

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**Guadalupe Manor  
Orange County, Annual**

**1.0 Project Characteristics**

**1.1 Land Usage**

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Retirement Community	29.00	Dwelling Unit	0.21	13,500.00	83

**1.2 Other Project Characteristics**

<b>Urbanization</b>	Urban	<b>Wind Speed (m/s)</b>	2.2	<b>Precipitation Freq (Days)</b>	30
<b>Climate Zone</b>	8			<b>Operational Year</b>	2024
<b>Utility Company</b>	Southern California Edison				
<b>CO2 Intensity (lb/MWhr)</b>	390.98	<b>CH4 Intensity (lb/MWhr)</b>	0.033	<b>N2O Intensity (lb/MWhr)</b>	0.004

**1.3 User Entered Comments & Non-Default Data**

- Project Characteristics -
- Land Use - site size 2.1 acres, only portion of site to be disturbed, 13,500 sf floor area
- Construction Phase -
- Vehicle Trips - 3.24 trips per unit per traffic analysis
- Construction Off-road Equipment Mitigation -
- Area Mitigation -
- Grading -

Table Name	Column Name	Default Value	New Value
tblLandUse	LandUseSquareFeet	29,000.00	13,500.00
tblLandUse	LotAcreage	5.80	0.21
tblVehicleTrips	ST_TR	2.03	3.24

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

tblVehicleTrips	SU_TR	1.95	3.24
tblVehicleTrips	WD_TR	2.40	3.24

**2.0 Emissions Summary**

**2.1 Overall Construction**

**Unmitigated Construction**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	tons/yr										MT/yr					
2024	0.0811	0.3595	0.4517	8.1000e-004	0.0190	0.0166	0.0357	6.2300e-003	0.0154	0.0216	0.0000	71.6045	71.6045	0.0186	6.0000e-004	72.2496
<b>Maximum</b>	<b>0.0811</b>	<b>0.3595</b>	<b>0.4517</b>	<b>8.1000e-004</b>	<b>0.0190</b>	<b>0.0166</b>	<b>0.0357</b>	<b>6.2300e-003</b>	<b>0.0154</b>	<b>0.0216</b>	<b>0.0000</b>	<b>71.6045</b>	<b>71.6045</b>	<b>0.0186</b>	<b>6.0000e-004</b>	<b>72.2496</b>

**Mitigated Construction**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	tons/yr										MT/yr					
2024	0.0811	0.3595	0.4517	8.1000e-004	0.0161	0.0166	0.0327	4.8200e-003	0.0154	0.0202	0.0000	71.6044	71.6044	0.0186	6.0000e-004	72.2495
<b>Maximum</b>	<b>0.0811</b>	<b>0.3595</b>	<b>0.4517</b>	<b>8.1000e-004</b>	<b>0.0161</b>	<b>0.0166</b>	<b>0.0327</b>	<b>4.8200e-003</b>	<b>0.0154</b>	<b>0.0202</b>	<b>0.0000</b>	<b>71.6044</b>	<b>71.6044</b>	<b>0.0186</b>	<b>6.0000e-004</b>	<b>72.2495</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N2O	CO2e
Percent Reduction	0.00	0.00	0.00	0.00	15.35	0.00	8.22	22.63	0.00	6.53	0.00	0.00	0.00	0.00	0.00	0.00

Quarter	Start Date	End Date	Maximum Unmitigated ROG + NOX (tons/quarter)	Maximum Mitigated ROG + NOX (tons/quarter)
1	1-1-2024	3-31-2024	0.2232	0.2232
2	4-1-2024	6-30-2024	0.2176	0.2176
		Highest	0.2232	0.2232

**2.2 Overall Operational**

**Unmitigated Operational**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Area	0.1570	0.0110	0.4833	4.9000e-004		0.0294	0.0294		0.0294	0.0294	3.0804	6.4079	9.4883	9.6500e-003	2.1000e-004	9.7919
Energy	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	40.8794	40.8794	2.2000e-003	5.7000e-004	41.1053
Mobile	0.0451	0.0513	0.4670	1.0900e-003	0.1210	7.5000e-004	0.1217	0.0323	7.0000e-004	0.0330	0.0000	100.9933	100.9933	6.1400e-003	4.2400e-003	102.4088
Waste						0.0000	0.0000		0.0000	0.0000	2.7079	0.0000	2.7079	0.1600	0.0000	6.7087
Water						0.0000	0.0000		0.0000	0.0000	0.5994	6.7102	7.3096	0.0621	1.5200e-003	9.3167
<b>Total</b>	<b>0.2040</b>	<b>0.0789</b>	<b>0.9573</b>	<b>1.6900e-003</b>	<b>0.1210</b>	<b>0.0314</b>	<b>0.1524</b>	<b>0.0323</b>	<b>0.0314</b>	<b>0.0637</b>	<b>6.3877</b>	<b>154.9908</b>	<b>161.3785</b>	<b>0.2402</b>	<b>6.5400e-003</b>	<b>169.3315</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**2.2 Overall Operational**

**Mitigated Operational**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Area	0.0626	8.8600e-003	0.3012	5.0000e-005		2.0900e-003	2.0900e-003		2.0900e-003	2.0900e-003	0.0000	6.7561	6.7561	5.9000e-004	1.1000e-004	6.8051
Energy	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	40.8794	40.8794	2.2000e-003	5.7000e-004	41.1053
Mobile	0.0451	0.0513	0.4670	1.0900e-003	0.1210	7.5000e-004	0.1217	0.0323	7.0000e-004	0.0330	0.0000	100.9933	100.9933	6.1400e-003	4.2400e-003	102.4088
Waste						0.0000	0.0000		0.0000	0.0000	2.7079	0.0000	2.7079	0.1600	0.0000	6.7087
Water						0.0000	0.0000		0.0000	0.0000	0.5994	6.7102	7.3096	0.0621	1.5200e-003	9.3167
<b>Total</b>	<b>0.1096</b>	<b>0.0768</b>	<b>0.7753</b>	<b>1.2500e-003</b>	<b>0.1210</b>	<b>4.1800e-003</b>	<b>0.1251</b>	<b>0.0323</b>	<b>4.1300e-003</b>	<b>0.0364</b>	<b>3.3073</b>	<b>155.3390</b>	<b>158.6463</b>	<b>0.2311</b>	<b>6.4400e-003</b>	<b>166.3446</b>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
<b>Percent Reduction</b>	<b>46.25</b>	<b>2.68</b>	<b>19.02</b>	<b>26.04</b>	<b>0.00</b>	<b>86.70</b>	<b>17.89</b>	<b>0.00</b>	<b>86.84</b>	<b>42.81</b>	<b>48.22</b>	<b>-0.22</b>	<b>1.69</b>	<b>3.77</b>	<b>1.53</b>	<b>1.76</b>

**3.0 Construction Detail**

**Construction Phase**

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Demolition	Demolition	1/1/2024	1/12/2024	5	10	
2	Grading	Grading	1/13/2024	1/16/2024	5	2	
3	Building Construction	Building Construction	1/17/2024	6/4/2024	5	100	

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

4	Paving	Paving	6/5/2024	6/11/2024	5	5
5	Architectural Coating	Architectural Coating	6/12/2024	6/18/2024	5	5

**Acres of Grading (Site Preparation Phase): 0**

**Acres of Grading (Grading Phase): 1.5**

**Acres of Paving: 0**

**Residential Indoor: 27,338; Residential Outdoor: 9,113; Non-Residential Indoor: 0; Non-Residential Outdoor: 0; Striped Parking Area: 0 (Architectural Coating – sqft)**

**OffRoad Equipment**

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	4	6.00	9	0.56
Demolition	Concrete/Industrial Saws	1	8.00	81	0.73
Building Construction	Cranes	1	4.00	231	0.29
Building Construction	Forklifts	2	6.00	89	0.20
Grading	Graders	1	6.00	187	0.41
Paving	Pavers	1	7.00	130	0.42
Paving	Rollers	1	7.00	80	0.38
Demolition	Rubber Tired Dozers	1	1.00	247	0.40
Grading	Rubber Tired Dozers	1	6.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	2	8.00	97	0.37
Demolition	Tractors/Loaders/Backhoes	2	6.00	97	0.37
Grading	Tractors/Loaders/Backhoes	1	7.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	7.00	97	0.37

**Trips and VMT**

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	4.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	5	21.00	3.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Demolition	4	10.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	3	8.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	7	18.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

**3.1 Mitigation Measures Construction**

Water Exposed Area

**3.2 Demolition - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	3.0800e-003	0.0274	0.0370	6.0000e-005		1.2500e-003	1.2500e-003		1.2000e-003	1.2000e-003	0.0000	5.2104	5.2104	9.4000e-004	0.0000	5.2339
<b>Total</b>	<b>3.0800e-003</b>	<b>0.0274</b>	<b>0.0370</b>	<b>6.0000e-005</b>		<b>1.2500e-003</b>	<b>1.2500e-003</b>		<b>1.2000e-003</b>	<b>1.2000e-003</b>	<b>0.0000</b>	<b>5.2104</b>	<b>5.2104</b>	<b>9.4000e-004</b>	<b>0.0000</b>	<b>5.2339</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.2 Demolition - 2024**

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.3000e-004	9.0000e-005	1.3500e-003	0.0000	5.5000e-004	0.0000	5.5000e-004	1.5000e-004	0.0000	1.5000e-004	0.0000	0.4041	0.4041	1.0000e-005	1.0000e-005	0.4071
<b>Total</b>	<b>1.3000e-004</b>	<b>9.0000e-005</b>	<b>1.3500e-003</b>	<b>0.0000</b>	<b>5.5000e-004</b>	<b>0.0000</b>	<b>5.5000e-004</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>0.4041</b>	<b>0.4041</b>	<b>1.0000e-005</b>	<b>1.0000e-005</b>	<b>0.4071</b>

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	3.0800e-003	0.0274	0.0370	6.0000e-005		1.2500e-003	1.2500e-003		1.2000e-003	1.2000e-003	0.0000	5.2104	5.2104	9.4000e-004	0.0000	5.2339
<b>Total</b>	<b>3.0800e-003</b>	<b>0.0274</b>	<b>0.0370</b>	<b>6.0000e-005</b>		<b>1.2500e-003</b>	<b>1.2500e-003</b>		<b>1.2000e-003</b>	<b>1.2000e-003</b>	<b>0.0000</b>	<b>5.2104</b>	<b>5.2104</b>	<b>9.4000e-004</b>	<b>0.0000</b>	<b>5.2339</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.2 Demolition - 2024**

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.3000e-004	9.0000e-005	1.3500e-003	0.0000	5.5000e-004	0.0000	5.5000e-004	1.5000e-004	0.0000	1.5000e-004	0.0000	0.4041	0.4041	1.0000e-005	1.0000e-005	0.4071
<b>Total</b>	<b>1.3000e-004</b>	<b>9.0000e-005</b>	<b>1.3500e-003</b>	<b>0.0000</b>	<b>5.5000e-004</b>	<b>0.0000</b>	<b>5.5000e-004</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>0.4041</b>	<b>0.4041</b>	<b>1.0000e-005</b>	<b>1.0000e-005</b>	<b>0.4071</b>

**3.3 Grading - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Fugitive Dust					5.3100e-003	0.0000	5.3100e-003	2.5700e-003	0.0000	2.5700e-003	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	9.1000e-004	9.7300e-003	5.5500e-003	1.0000e-005		4.0000e-004	4.0000e-004		3.7000e-004	3.7000e-004	0.0000	1.2380	1.2380	4.0000e-004	0.0000	1.2480
<b>Total</b>	<b>9.1000e-004</b>	<b>9.7300e-003</b>	<b>5.5500e-003</b>	<b>1.0000e-005</b>	<b>5.3100e-003</b>	<b>4.0000e-004</b>	<b>5.7100e-003</b>	<b>2.5700e-003</b>	<b>3.7000e-004</b>	<b>2.9400e-003</b>	<b>0.0000</b>	<b>1.2380</b>	<b>1.2380</b>	<b>4.0000e-004</b>	<b>0.0000</b>	<b>1.2480</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.3 Grading - 2024**

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	2.0000e-005	1.0000e-005	2.2000e-004	0.0000	9.0000e-005	0.0000	9.0000e-005	2.0000e-005	0.0000	2.0000e-005	0.0000	0.0647	0.0647	0.0000	0.0000	0.0651
<b>Total</b>	<b>2.0000e-005</b>	<b>1.0000e-005</b>	<b>2.2000e-004</b>	<b>0.0000</b>	<b>9.0000e-005</b>	<b>0.0000</b>	<b>9.0000e-005</b>	<b>2.0000e-005</b>	<b>0.0000</b>	<b>2.0000e-005</b>	<b>0.0000</b>	<b>0.0647</b>	<b>0.0647</b>	<b>0.0000</b>	<b>0.0000</b>	<b>0.0651</b>

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Fugitive Dust					2.3900e-003	0.0000	2.3900e-003	1.1600e-003	0.0000	1.1600e-003	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	9.1000e-004	9.7300e-003	5.5500e-003	1.0000e-005		4.0000e-004	4.0000e-004		3.7000e-004	3.7000e-004	0.0000	1.2380	1.2380	4.0000e-004	0.0000	1.2480
<b>Total</b>	<b>9.1000e-004</b>	<b>9.7300e-003</b>	<b>5.5500e-003</b>	<b>1.0000e-005</b>	<b>2.3900e-003</b>	<b>4.0000e-004</b>	<b>2.7900e-003</b>	<b>1.1600e-003</b>	<b>3.7000e-004</b>	<b>1.5300e-003</b>	<b>0.0000</b>	<b>1.2380</b>	<b>1.2380</b>	<b>4.0000e-004</b>	<b>0.0000</b>	<b>1.2480</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.3 Grading - 2024**

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	2.0000e-005	1.0000e-005	2.2000e-004	0.0000	9.0000e-005	0.0000	9.0000e-005	2.0000e-005	0.0000	2.0000e-005	0.0000	0.0647	0.0647	0.0000	0.0000	0.0651
<b>Total</b>	<b>2.0000e-005</b>	<b>1.0000e-005</b>	<b>2.2000e-004</b>	<b>0.0000</b>	<b>9.0000e-005</b>	<b>0.0000</b>	<b>9.0000e-005</b>	<b>2.0000e-005</b>	<b>0.0000</b>	<b>2.0000e-005</b>	<b>0.0000</b>	<b>0.0647</b>	<b>0.0647</b>	<b>0.0000</b>	<b>0.0000</b>	<b>0.0651</b>

**3.4 Building Construction - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	0.0298	0.2987	0.3534	5.7000e-004		0.0141	0.0141		0.0130	0.0130	0.0000	50.1212	50.1212	0.0162	0.0000	50.5265
<b>Total</b>	<b>0.0298</b>	<b>0.2987</b>	<b>0.3534</b>	<b>5.7000e-004</b>		<b>0.0141</b>	<b>0.0141</b>		<b>0.0130</b>	<b>0.0130</b>	<b>0.0000</b>	<b>50.1212</b>	<b>50.1212</b>	<b>0.0162</b>	<b>0.0000</b>	<b>50.5265</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.4 Building Construction - 2024**

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	1.5000e-004	5.4900e-003	2.1900e-003	3.0000e-005	9.5000e-004	3.0000e-005	9.7000e-004	2.7000e-004	3.0000e-005	3.0000e-004	0.0000	2.6468	2.6468	1.6000e-004	3.8000e-004	2.7646
Worker	2.7900e-003	1.9000e-003	0.0285	9.0000e-005	0.0115	6.0000e-005	0.0116	3.0600e-003	5.0000e-005	3.1100e-003	0.0000	8.4863	8.4863	1.9000e-004	2.0000e-004	8.5499
<b>Total</b>	<b>2.9400e-003</b>	<b>7.3900e-003</b>	<b>0.0306</b>	<b>1.2000e-004</b>	<b>0.0125</b>	<b>9.0000e-005</b>	<b>0.0126</b>	<b>3.3300e-003</b>	<b>8.0000e-005</b>	<b>3.4100e-003</b>	<b>0.0000</b>	<b>11.1332</b>	<b>11.1332</b>	<b>3.5000e-004</b>	<b>5.8000e-004</b>	<b>11.3146</b>

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	0.0298	0.2987	0.3534	5.7000e-004		0.0141	0.0141		0.0130	0.0130	0.0000	50.1211	50.1211	0.0162	0.0000	50.5264
<b>Total</b>	<b>0.0298</b>	<b>0.2987</b>	<b>0.3534</b>	<b>5.7000e-004</b>		<b>0.0141</b>	<b>0.0141</b>		<b>0.0130</b>	<b>0.0130</b>	<b>0.0000</b>	<b>50.1211</b>	<b>50.1211</b>	<b>0.0162</b>	<b>0.0000</b>	<b>50.5264</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.4 Building Construction - 2024**

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	1.5000e-004	5.4900e-003	2.1900e-003	3.0000e-005	9.5000e-004	3.0000e-005	9.7000e-004	2.7000e-004	3.0000e-005	3.0000e-004	0.0000	2.6468	2.6468	1.6000e-004	3.8000e-004	2.7646
Worker	2.7900e-003	1.9000e-003	0.0285	9.0000e-005	0.0115	6.0000e-005	0.0116	3.0600e-003	5.0000e-005	3.1100e-003	0.0000	8.4863	8.4863	1.9000e-004	2.0000e-004	8.5499
<b>Total</b>	<b>2.9400e-003</b>	<b>7.3900e-003</b>	<b>0.0306</b>	<b>1.2000e-004</b>	<b>0.0125</b>	<b>9.0000e-005</b>	<b>0.0126</b>	<b>3.3300e-003</b>	<b>8.0000e-005</b>	<b>3.4100e-003</b>	<b>0.0000</b>	<b>11.1332</b>	<b>11.1332</b>	<b>3.5000e-004</b>	<b>5.8000e-004</b>	<b>11.3146</b>

**3.5 Paving - 2024**

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	1.4800e-003	0.0131	0.0176	3.0000e-005		6.1000e-004	6.1000e-004		5.7000e-004	5.7000e-004	0.0000	2.3502	2.3502	6.8000e-004	0.0000	2.3673
Paving	0.0000					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
<b>Total</b>	<b>1.4800e-003</b>	<b>0.0131</b>	<b>0.0176</b>	<b>3.0000e-005</b>		<b>6.1000e-004</b>	<b>6.1000e-004</b>		<b>5.7000e-004</b>	<b>5.7000e-004</b>	<b>0.0000</b>	<b>2.3502</b>	<b>2.3502</b>	<b>6.8000e-004</b>	<b>0.0000</b>	<b>2.3673</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.5 Paving - 2024**

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.2000e-004	8.0000e-005	1.2200e-003	0.0000	4.9000e-004	0.0000	5.0000e-004	1.3000e-004	0.0000	1.3000e-004	0.0000	0.3637	0.3637	1.0000e-005	1.0000e-005	0.3664
<b>Total</b>	<b>1.2000e-004</b>	<b>8.0000e-005</b>	<b>1.2200e-003</b>	<b>0.0000</b>	<b>4.9000e-004</b>	<b>0.0000</b>	<b>5.0000e-004</b>	<b>1.3000e-004</b>	<b>0.0000</b>	<b>1.3000e-004</b>	<b>0.0000</b>	<b>0.3637</b>	<b>0.3637</b>	<b>1.0000e-005</b>	<b>1.0000e-005</b>	<b>0.3664</b>

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Off-Road	1.4800e-003	0.0131	0.0176	3.0000e-005		6.1000e-004	6.1000e-004		5.7000e-004	5.7000e-004	0.0000	2.3502	2.3502	6.8000e-004	0.0000	2.3673
Paving	0.0000					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
<b>Total</b>	<b>1.4800e-003</b>	<b>0.0131</b>	<b>0.0176</b>	<b>3.0000e-005</b>		<b>6.1000e-004</b>	<b>6.1000e-004</b>		<b>5.7000e-004</b>	<b>5.7000e-004</b>	<b>0.0000</b>	<b>2.3502</b>	<b>2.3502</b>	<b>6.8000e-004</b>	<b>0.0000</b>	<b>2.3673</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.5 Paving - 2024**

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	1.2000e-004	8.0000e-005	1.2200e-003	0.0000	4.9000e-004	0.0000	5.0000e-004	1.3000e-004	0.0000	1.3000e-004	0.0000	0.3637	0.3637	1.0000e-005	1.0000e-005	0.3664
<b>Total</b>	<b>1.2000e-004</b>	<b>8.0000e-005</b>	<b>1.2200e-003</b>	<b>0.0000</b>	<b>4.9000e-004</b>	<b>0.0000</b>	<b>5.0000e-004</b>	<b>1.3000e-004</b>	<b>0.0000</b>	<b>1.3000e-004</b>	<b>0.0000</b>	<b>0.3637</b>	<b>0.3637</b>	<b>1.0000e-005</b>	<b>1.0000e-005</b>	<b>0.3664</b>

**3.6 Architectural Coating - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Archit. Coating	0.0422					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	4.5000e-004	3.0500e-003	4.5300e-003	1.0000e-005		1.5000e-004	1.5000e-004		1.5000e-004	1.5000e-004	0.0000	0.6383	0.6383	4.0000e-005	0.0000	0.6392
<b>Total</b>	<b>0.0427</b>	<b>3.0500e-003</b>	<b>4.5300e-003</b>	<b>1.0000e-005</b>		<b>1.5000e-004</b>	<b>1.5000e-004</b>		<b>1.5000e-004</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>0.6383</b>	<b>0.6383</b>	<b>4.0000e-005</b>	<b>0.0000</b>	<b>0.6392</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.6 Architectural Coating - 2024**

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	3.0000e-005	2.0000e-005	2.7000e-004	0.0000	1.1000e-004	0.0000	1.1000e-004	3.0000e-005	0.0000	3.0000e-005	0.0000	0.0808	0.0808	0.0000	0.0000	0.0814
<b>Total</b>	<b>3.0000e-005</b>	<b>2.0000e-005</b>	<b>2.7000e-004</b>	<b>0.0000</b>	<b>1.1000e-004</b>	<b>0.0000</b>	<b>1.1000e-004</b>	<b>3.0000e-005</b>	<b>0.0000</b>	<b>3.0000e-005</b>	<b>0.0000</b>	<b>0.0808</b>	<b>0.0808</b>	<b>0.0000</b>	<b>0.0000</b>	<b>0.0814</b>

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Archit. Coating	0.0422					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Off-Road	4.5000e-004	3.0500e-003	4.5300e-003	1.0000e-005		1.5000e-004	1.5000e-004		1.5000e-004	1.5000e-004	0.0000	0.6383	0.6383	4.0000e-005	0.0000	0.6392
<b>Total</b>	<b>0.0427</b>	<b>3.0500e-003</b>	<b>4.5300e-003</b>	<b>1.0000e-005</b>		<b>1.5000e-004</b>	<b>1.5000e-004</b>		<b>1.5000e-004</b>	<b>1.5000e-004</b>	<b>0.0000</b>	<b>0.6383</b>	<b>0.6383</b>	<b>4.0000e-005</b>	<b>0.0000</b>	<b>0.6392</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.6 Architectural Coating - 2024**

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	tons/yr										MT/yr						
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Worker	3.0000e-005	2.0000e-005	2.7000e-004	0.0000	1.1000e-004	0.0000	1.1000e-004	3.0000e-005	0.0000	3.0000e-005	0.0000	0.0808	0.0808	0.0000	0.0000	0.0814	0.0814
<b>Total</b>	<b>3.0000e-005</b>	<b>2.0000e-005</b>	<b>2.7000e-004</b>	<b>0.0000</b>	<b>1.1000e-004</b>	<b>0.0000</b>	<b>1.1000e-004</b>	<b>3.0000e-005</b>	<b>0.0000</b>	<b>3.0000e-005</b>	<b>0.0000</b>	<b>0.0808</b>	<b>0.0808</b>	<b>0.0000</b>	<b>0.0000</b>	<b>0.0814</b>	<b>0.0814</b>

Guadalupe Manor - Orange County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied

4.0 Operational Detail - Mobile

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Mitigated	0.0451	0.0513	0.4670	1.0900e-003	0.1210	7.5000e-004	0.1217	0.0323	7.0000e-004	0.0330	0.0000	100.9933	100.9933	6.1400e-003	4.2400e-003	102.4088
Unmitigated	0.0451	0.0513	0.4670	1.0900e-003	0.1210	7.5000e-004	0.1217	0.0323	7.0000e-004	0.0330	0.0000	100.9933	100.9933	6.1400e-003	4.2400e-003	102.4088

4.2 Trip Summary Information

Land Use	Average Daily Trip Rate			Unmitigated	Mitigated
	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Retirement Community	93.96	93.96	93.96	321,076	321,076
Total	93.96	93.96	93.96	321,076	321,076

4.3 Trip Type Information

Land Use	Miles			Trip %			Trip Purpose %		
	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Retirement Community	14.70	5.90	8.70	40.20	19.20	40.60	86	11	3

4.4 Fleet Mix

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Retirement Community	0.546200	0.059546	0.185910	0.127866	0.024295	0.006605	0.014499	0.004906	0.000657	0.000381	0.024552	0.000713	0.003869

Guadalupe Manor - Orange County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied

5.0 Energy Detail

Historical Energy Use: N

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Electricity Mitigated						0.0000	0.0000		0.0000	0.0000	0.0000	21.6601	21.6601	1.8300e-003	2.2000e-004	21.7719
Electricity Unmitigated						0.0000	0.0000		0.0000	0.0000	0.0000	21.6601	21.6601	1.8300e-003	2.2000e-004	21.7719
NaturalGas Mitigated	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	19.2193	19.2193	3.7000e-004	3.5000e-004	19.3335
NaturalGas Unmitigated	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	19.2193	19.2193	3.7000e-004	3.5000e-004	19.3335

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**5.2 Energy by Land Use - NaturalGas**

**Unmitigated**

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	tons/yr										MT/yr					
Retirement Community	360155	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	19.2193	19.2193	3.7000e-004	3.5000e-004	19.3335
<b>Total</b>		<b>1.9400e-003</b>	<b>0.0166</b>	<b>7.0600e-003</b>	<b>1.1000e-004</b>		<b>1.3400e-003</b>	<b>1.3400e-003</b>		<b>1.3400e-003</b>	<b>1.3400e-003</b>	<b>0.0000</b>	<b>19.2193</b>	<b>19.2193</b>	<b>3.7000e-004</b>	<b>3.5000e-004</b>	<b>19.3335</b>

**Mitigated**

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	tons/yr										MT/yr					
Retirement Community	360155	1.9400e-003	0.0166	7.0600e-003	1.1000e-004		1.3400e-003	1.3400e-003		1.3400e-003	1.3400e-003	0.0000	19.2193	19.2193	3.7000e-004	3.5000e-004	19.3335
<b>Total</b>		<b>1.9400e-003</b>	<b>0.0166</b>	<b>7.0600e-003</b>	<b>1.1000e-004</b>		<b>1.3400e-003</b>	<b>1.3400e-003</b>		<b>1.3400e-003</b>	<b>1.3400e-003</b>	<b>0.0000</b>	<b>19.2193</b>	<b>19.2193</b>	<b>3.7000e-004</b>	<b>3.5000e-004</b>	<b>19.3335</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**5.3 Energy by Land Use - Electricity**

**Unmitigated**

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr	MT/yr			
Retirement Community	122135	21.6601	1.8300e-003	2.2000e-004	21.7719
<b>Total</b>		<b>21.6601</b>	<b>1.8300e-003</b>	<b>2.2000e-004</b>	<b>21.7719</b>

**Mitigated**

	Electricity Use	Total CO2	CH4	N2O	CO2e
Land Use	kWh/yr	MT/yr			
Retirement Community	122135	21.6601	1.8300e-003	2.2000e-004	21.7719
<b>Total</b>		<b>21.6601</b>	<b>1.8300e-003</b>	<b>2.2000e-004</b>	<b>21.7719</b>

**6.0 Area Detail**

**6.1 Mitigation Measures Area**

Use only Natural Gas Hearths

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	tons/yr										MT/yr					
Mitigated	0.0626	8.8600e-003	0.3012	5.0000e-005		2.0900e-003	2.0900e-003		2.0900e-003	2.0900e-003	0.0000	6.7561	6.7561	5.9000e-004	1.1000e-004	6.8051
Unmitigated	0.1570	0.0110	0.4833	4.9000e-004		0.0294	0.0294		0.0294	0.0294	3.0804	6.4079	9.4883	9.6500e-003	2.1000e-004	9.7919

**6.2 Area by SubCategory**

**Unmitigated**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	tons/yr										MT/yr					
Architectural Coating	4.2200e-003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Consumer Products	0.0488					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Hearth	0.0950	7.5200e-003	0.1844	4.7000e-004		0.0277	0.0277		0.0277	0.0277	3.0804	5.9194	8.9997	9.1900e-003	2.1000e-004	9.2917
Landscaping	8.9900e-003	3.4400e-003	0.2989	2.0000e-005		1.6600e-003	1.6600e-003		1.6600e-003	1.6600e-003	0.0000	0.4885	0.4885	4.7000e-004	0.0000	0.5002
<b>Total</b>	<b>0.1570</b>	<b>0.0110</b>	<b>0.4833</b>	<b>4.9000e-004</b>		<b>0.0294</b>	<b>0.0294</b>		<b>0.0294</b>	<b>0.0294</b>	<b>3.0804</b>	<b>6.4079</b>	<b>9.4883</b>	<b>9.6600e-003</b>	<b>2.1000e-004</b>	<b>9.7919</b>

Guadalupe Manor - Orange County, Annual

EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	tons/yr										MT/yr					
Architectural Coating	4.2200e-003					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Consumer Products	0.0488					0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Hearth	6.3000e-004	5.4100e-003	2.3000e-003	3.0000e-005		4.4000e-004	4.4000e-004		4.4000e-004	4.4000e-004	0.0000	6.2676	6.2676	1.2000e-004	1.1000e-004	6.3048
Landscaping	8.9900e-003	3.4400e-003	0.2989	2.0000e-005		1.6600e-003	1.6600e-003		1.6600e-003	1.6600e-003	0.0000	0.4885	0.4885	4.7000e-004	0.0000	0.5002
<b>Total</b>	<b>0.0626</b>	<b>8.8500e-003</b>	<b>0.3012</b>	<b>5.0000e-005</b>		<b>2.1000e-003</b>	<b>2.1000e-003</b>		<b>2.1000e-003</b>	<b>2.1000e-003</b>	<b>0.0000</b>	<b>6.7561</b>	<b>6.7561</b>	<b>5.9000e-004</b>	<b>1.1000e-004</b>	<b>6.8051</b>

7.0 Water Detail

7.1 Mitigation Measures Water

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

	Total CO2	CH4	N2O	CO2e
Category	MT/yr			
Mitigated	7.3096	0.0621	1.5200e-003	9.3167
Unmitigated	7.3096	0.0621	1.5200e-003	9.3167

**7.2 Water by Land Use**

**Unmitigated**

	Indoor/Outdoor Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal	MT/yr			
Retirement Community	1.88947 / 1.19119	7.3096	0.0621	1.5200e-003	9.3167
<b>Total</b>		<b>7.3096</b>	<b>0.0621</b>	<b>1.5200e-003</b>	<b>9.3167</b>

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**7.2 Water by Land Use**

Mitigated

	Indoor/Outdoor Use	Total CO2	CH4	N2O	CO2e
Land Use	Mgal	MT/yr			
Retirement Community	1.88947 / 1.19119	7.3096	0.0621	1.5200e-003	9.3167
<b>Total</b>		<b>7.3096</b>	<b>0.0621</b>	<b>1.5200e-003</b>	<b>9.3167</b>

**8.0 Waste Detail**

---

**8.1 Mitigation Measures Waste**

Category/Year

	Total CO2	CH4	N2O	CO2e
	MT/yr			
Mitigated	2.7079	0.1600	0.0000	6.7087
Unmitigated	2.7079	0.1600	0.0000	6.7087

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**8.2 Waste by Land Use**

Unmitigated

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons	MT/yr			
Retirement Community	13.34	2.7079	0.1600	0.0000	6.7087
<b>Total</b>		<b>2.7079</b>	<b>0.1600</b>	<b>0.0000</b>	<b>6.7087</b>

Mitigated

	Waste Disposed	Total CO2	CH4	N2O	CO2e
Land Use	tons	MT/yr			
Retirement Community	13.34	2.7079	0.1600	0.0000	6.7087
<b>Total</b>		<b>2.7079</b>	<b>0.1600</b>	<b>0.0000</b>	<b>6.7087</b>

**9.0 Operational Offroad**

---

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	-----------	-------------	-------------	-----------

Guadalupe Manor - Orange County, Annual

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**10.0 Stationary Equipment**

---

**Fire Pumps and Emergency Generators**

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	------------	-------------	-------------	-----------

**Boilers**

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type
----------------	--------	----------------	-----------------	---------------	-----------

**User Defined Equipment**

Equipment Type	Number
----------------	--------

**11.0 Vegetation**

---

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**Guadalupe Manor  
Orange County, Summer**

**1.0 Project Characteristics**

**1.1 Land Usage**

Land Uses	Size	Metric	Lot Acreage	Floor Surface Area	Population
Retirement Community	29.00	Dwelling Unit	0.21	13,500.00	83

**1.2 Other Project Characteristics**

<b>Urbanization</b>	Urban	<b>Wind Speed (m/s)</b>	2.2	<b>Precipitation Freq (Days)</b>	30
<b>Climate Zone</b>	8			<b>Operational Year</b>	2024
<b>Utility Company</b>	Southern California Edison				
<b>CO2 Intensity (lb/MW hr)</b>	390.98	<b>CH4 Intensity (lb/MW hr)</b>	0.033	<b>N2O Intensity (lb/MW hr)</b>	0.004

**1.3 User Entered Comments & Non-Default Data**

- Project Characteristics -
- Land Use - site size 2.1 acres, only portion of site to be disturbed, 13,500 sf floor area
- Construction Phase -
- Vehicle Trips - 3.24 trips per unit per traffic analysis
- Construction Off-road Equipment Mitigation -
- Area Mitigation -
- Grading -

Table Name	Column Name	Default Value	New Value
tblLandUse	LandUseSquareFeet	29,000.00	13,500.00
tblLandUse	LotAcreage	5.80	0.21
tblVehicleTrips	ST_TR	2.03	3.24

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

tblVehicleTrips	SU_TR	1.95	3.24
tblVehicleTrips	WD_TR	2.40	3.24

**2.0 Emissions Summary**

**2.1 Overall Construction (Maximum Daily Emission)**

Unmitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	lb/day										lb/day					
2024	17.0864	9.7427	7.7075	0.0148	5.4014	0.4005	5.8019	2.5923	0.3685	2.9608	0.0000	1,438.5090	1,438.5090	0.4429	0.0125	1,450.0402
Maximum	17.0864	9.7427	7.7075	0.0148	5.4014	0.4005	5.8019	2.5923	0.3685	2.9608	0.0000	1,438.5090	1,438.5090	0.4429	0.0125	1,450.0402

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	lb/day										lb/day					
2024	17.0864	9.7427	7.7075	0.0148	2.4798	0.4005	2.8803	1.1796	0.3685	1.5481	0.0000	1,438.5090	1,438.5090	0.4429	0.0125	1,450.0402
Maximum	17.0864	9.7427	7.7075	0.0148	2.4798	0.4005	2.8803	1.1796	0.3685	1.5481	0.0000	1,438.5090	1,438.5090	0.4429	0.0125	1,450.0402



Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**2.2 Overall Operational**

**Unmitigated Operational**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	7.9614	0.6293	17.1395	0.0378		2.2285	2.2285		2.2285	2.2285	271.6406	526.3080	797.9487	0.8142	0.0184	823.7984
Energy	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753
Mobile	0.2546	0.2587	2.5796	6.1900e-003	0.6765	4.1200e-003	0.6807	0.1803	3.8300e-003	0.1842		629.9123	629.9123	0.0362	0.0245	638.1164
<b>Total</b>	<b>8.2267</b>	<b>0.9789</b>	<b>19.7579</b>	<b>0.0445</b>	<b>0.6765</b>	<b>2.2400</b>	<b>2.9165</b>	<b>0.1803</b>	<b>2.2397</b>	<b>2.4200</b>	<b>271.6406</b>	<b>1,272.3057</b>	<b>1,543.9463</b>	<b>0.8527</b>	<b>0.0451</b>	<b>1,578.6900</b>

**Mitigated Operational**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Area	0.4130	0.4605	2.5758	2.8900e-003		0.0483	0.0483		0.0483	0.0483	0.0000	557.0139	557.0139	0.0147	0.0101	560.4017
Energy	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753
Mobile	0.2546	0.2587	2.5796	6.1900e-003	0.6765	4.1200e-003	0.6807	0.1803	3.8300e-003	0.1842		629.9123	629.9123	0.0362	0.0245	638.1164
<b>Total</b>	<b>0.6783</b>	<b>0.8102</b>	<b>5.1941</b>	<b>9.6600e-003</b>	<b>0.6765</b>	<b>0.0597</b>	<b>0.7363</b>	<b>0.1803</b>	<b>0.0594</b>	<b>0.2398</b>	<b>0.0000</b>	<b>1,303.0116</b>	<b>1,303.0116</b>	<b>0.0532</b>	<b>0.0368</b>	<b>1,315.2934</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio-CO2	Total CO2	CH4	N2O	CO2e
Percent Reduction	91.75	17.24	73.71	78.30	0.00	97.33	74.76	0.00	97.35	90.09	100.00	-2.41	15.61	93.76	18.44	16.68

**3.0 Construction Detail**

**Construction Phase**

Phase Number	Phase Name	Phase Type	Start Date	End Date	Num Days Week	Num Days	Phase Description
1	Demolition	Demolition	1/1/2024	1/12/2024	5	10	
2	Grading	Grading	1/13/2024	1/16/2024	5	2	
3	Building Construction	Building Construction	1/17/2024	6/4/2024	5	100	
4	Paving	Paving	6/5/2024	6/11/2024	5	5	
5	Architectural Coating	Architectural Coating	6/12/2024	6/18/2024	5	5	

**Acres of Grading (Site Preparation Phase): 0**

**Acres of Grading (Grading Phase): 1.5**

**Acres of Paving: 0**

**Residential Indoor: 27,338; Residential Outdoor: 9,113; Non-Residential Indoor: 0; Non-Residential Outdoor: 0; Striped Parking Area: 0 (Architectural Coating – sqft)**

**OffRoad Equipment**

Phase Name	Offroad Equipment Type	Amount	Usage Hours	Horse Power	Load Factor
Architectural Coating	Air Compressors	1	6.00	78	0.48
Paving	Cement and Mortar Mixers	4	6.00	9	0.56
Demolition	Concrete/Industrial Saws	1	8.00	81	0.73
Building Construction	Cranes	1	4.00	231	0.29
Building Construction	Forklifts	2	6.00	89	0.20
Grading	Graders	1	6.00	187	0.41

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

Paving	Pavers	1	7.00	130	0.42
Paving	Rollers	1	7.00	80	0.38
Demolition	Rubber Tired Dozers	1	1.00	247	0.40
Grading	Rubber Tired Dozers	1	6.00	247	0.40
Building Construction	Tractors/Loaders/Backhoes	2	8.00	97	0.37
Demolition	Tractors/Loaders/Backhoes	2	6.00	97	0.37
Grading	Tractors/Loaders/Backhoes	1	7.00	97	0.37
Paving	Tractors/Loaders/Backhoes	1	7.00	97	0.37

**Trips and VMT**

Phase Name	Offroad Equipment Count	Worker Trip Number	Vendor Trip Number	Hauling Trip Number	Worker Trip Length	Vendor Trip Length	Hauling Trip Length	Worker Vehicle Class	Vendor Vehicle Class	Hauling Vehicle Class
Architectural Coating	1	4.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Building Construction	5	21.00	3.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Demolition	4	10.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Grading	3	8.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT
Paving	7	18.00	0.00	0.00	14.70	6.90	20.00	LD_Mix	HDT_Mix	HHDT

**3.1 Mitigation Measures Construction**

Water Exposed Area

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.2 Demolition - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.6156	5.4776	7.3949	0.0120		0.2504	0.2504		0.2392	0.2392		1,148.6874	1,148.6874	0.2080		1,153.8870
<b>Total</b>	<b>0.6156</b>	<b>5.4776</b>	<b>7.3949</b>	<b>0.0120</b>		<b>0.2504</b>	<b>0.2504</b>		<b>0.2392</b>	<b>0.2392</b>		<b>1,148.6874</b>	<b>1,148.6874</b>	<b>0.2080</b>		<b>1,153.8870</b>

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0265	0.0162	0.2842	9.1000e-004	0.1118	5.4000e-004	0.1123	0.0296	5.0000e-004	0.0301		92.3085	92.3085	1.9000e-003	1.9300e-003	92.9300
<b>Total</b>	<b>0.0265</b>	<b>0.0162</b>	<b>0.2842</b>	<b>9.1000e-004</b>	<b>0.1118</b>	<b>5.4000e-004</b>	<b>0.1123</b>	<b>0.0296</b>	<b>5.0000e-004</b>	<b>0.0301</b>		<b>92.3085</b>	<b>92.3085</b>	<b>1.9000e-003</b>	<b>1.9300e-003</b>	<b>92.9300</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.2 Demolition - 2024**

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.6156	5.4776	7.3949	0.0120		0.2504	0.2504		0.2392	0.2392	0.0000	1,148.6874	1,148.6874	0.2080		1,153.8870
<b>Total</b>	<b>0.6156</b>	<b>5.4776</b>	<b>7.3949</b>	<b>0.0120</b>		<b>0.2504</b>	<b>0.2504</b>		<b>0.2392</b>	<b>0.2392</b>	<b>0.0000</b>	<b>1,148.6874</b>	<b>1,148.6874</b>	<b>0.2080</b>		<b>1,153.8870</b>

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0265	0.0162	0.2842	9.1000e-004	0.1118	5.4000e-004	0.1123	0.0296	5.0000e-004	0.0301		92.3085	92.3085	1.9000e-003	1.9300e-003	92.9300
<b>Total</b>	<b>0.0265</b>	<b>0.0162</b>	<b>0.2842</b>	<b>9.1000e-004</b>	<b>0.1118</b>	<b>5.4000e-004</b>	<b>0.1123</b>	<b>0.0296</b>	<b>5.0000e-004</b>	<b>0.0301</b>		<b>92.3085</b>	<b>92.3085</b>	<b>1.9000e-003</b>	<b>1.9300e-003</b>	<b>92.9300</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.3 Grading - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					5.3119	0.0000	5.3119	2.5686	0.0000	2.5686			0.0000			0.0000
Off-Road	0.9132	9.7297	5.5468	0.0141		0.4001	0.4001		0.3681	0.3681		1,364.662 3	1,364.662 3	0.4414		1,375.696 2
<b>Total</b>	<b>0.9132</b>	<b>9.7297</b>	<b>5.5468</b>	<b>0.0141</b>	<b>5.3119</b>	<b>0.4001</b>	<b>5.7120</b>	<b>2.5686</b>	<b>0.3681</b>	<b>2.9367</b>		<b>1,364.662 3</b>	<b>1,364.662 3</b>	<b>0.4414</b>		<b>1,375.696 2</b>

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0212	0.0129	0.2273	7.3000e-004	0.0894	4.3000e-004	0.0899	0.0237	4.0000e-004	0.0241		73.8468	73.8468	1.5200e-003	1.5400e-003	74.3440
<b>Total</b>	<b>0.0212</b>	<b>0.0129</b>	<b>0.2273</b>	<b>7.3000e-004</b>	<b>0.0894</b>	<b>4.3000e-004</b>	<b>0.0899</b>	<b>0.0237</b>	<b>4.0000e-004</b>	<b>0.0241</b>		<b>73.8468</b>	<b>73.8468</b>	<b>1.5200e-003</b>	<b>1.5400e-003</b>	<b>74.3440</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.3 Grading - 2024**

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Fugitive Dust					2.3904	0.0000	2.3904	1.1559	0.0000	1.1559			0.0000			0.0000
Off-Road	0.9132	9.7297	5.5468	0.0141		0.4001	0.4001		0.3681	0.3681	0.0000	1,364.662 3	1,364.662 3	0.4414		1,375.696 2
<b>Total</b>	<b>0.9132</b>	<b>9.7297</b>	<b>5.5468</b>	<b>0.0141</b>	<b>2.3904</b>	<b>0.4001</b>	<b>2.7905</b>	<b>1.1559</b>	<b>0.3681</b>	<b>1.5240</b>	<b>0.0000</b>	<b>1,364.662 3</b>	<b>1,364.662 3</b>	<b>0.4414</b>		<b>1,375.696 2</b>

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0212	0.0129	0.2273	7.3000e-004	0.0894	4.3000e-004	0.0899	0.0237	4.0000e-004	0.0241		73.8468	73.8468	1.5200e-003	1.5400e-003	74.3440
<b>Total</b>	<b>0.0212</b>	<b>0.0129</b>	<b>0.2273</b>	<b>7.3000e-004</b>	<b>0.0894</b>	<b>4.3000e-004</b>	<b>0.0899</b>	<b>0.0237</b>	<b>4.0000e-004</b>	<b>0.0241</b>		<b>73.8468</b>	<b>73.8468</b>	<b>1.5200e-003</b>	<b>1.5400e-003</b>	<b>74.3440</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.4 Building Construction - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.5950	5.9739	7.0675	0.0114		0.2824	0.2824		0.2598	0.2598		1,104.9834	1,104.9834	0.3574		1,113.9177
<b>Total</b>	<b>0.5950</b>	<b>5.9739</b>	<b>7.0675</b>	<b>0.0114</b>		<b>0.2824</b>	<b>0.2824</b>		<b>0.2598</b>	<b>0.2598</b>		<b>1,104.9834</b>	<b>1,104.9834</b>	<b>0.3574</b>		<b>1,113.9177</b>

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	2.9800e-003	0.1048	0.0433	5.3000e-004	0.0192	5.6000e-004	0.0198	5.5200e-003	5.4000e-004	6.0600e-003		58.3159	58.3159	3.5600e-003	8.4000e-003	60.9090
Worker	0.0556	0.0340	0.5967	1.9200e-003	0.2347	1.1400e-003	0.2359	0.0623	1.0500e-003	0.0633		193.8478	193.8478	3.9900e-003	4.0500e-003	195.1530
<b>Total</b>	<b>0.0586</b>	<b>0.1388</b>	<b>0.6400</b>	<b>2.4500e-003</b>	<b>0.2539</b>	<b>1.7000e-003</b>	<b>0.2556</b>	<b>0.0678</b>	<b>1.5900e-003</b>	<b>0.0694</b>		<b>252.1637</b>	<b>252.1637</b>	<b>7.5500e-003</b>	<b>0.0125</b>	<b>256.0620</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.4 Building Construction - 2024**

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.5950	5.9739	7.0675	0.0114		0.2824	0.2824		0.2598	0.2598	0.0000	1,104.9834	1,104.9834	0.3574		1,113.9177
<b>Total</b>	<b>0.5950</b>	<b>5.9739</b>	<b>7.0675</b>	<b>0.0114</b>		<b>0.2824</b>	<b>0.2824</b>		<b>0.2598</b>	<b>0.2598</b>	<b>0.0000</b>	<b>1,104.9834</b>	<b>1,104.9834</b>	<b>0.3574</b>		<b>1,113.9177</b>

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	2.9800e-003	0.1048	0.0433	5.3000e-004	0.0192	5.6000e-004	0.0198	5.5200e-003	5.4000e-004	6.0600e-003		58.3159	58.3159	3.5600e-003	8.4000e-003	60.9090
Worker	0.0556	0.0340	0.5967	1.9200e-003	0.2347	1.1400e-003	0.2359	0.0623	1.0500e-003	0.0633		193.8478	193.8478	3.9900e-003	4.0500e-003	195.1530
<b>Total</b>	<b>0.0586</b>	<b>0.1388</b>	<b>0.6400</b>	<b>2.4500e-003</b>	<b>0.2539</b>	<b>1.7000e-003</b>	<b>0.2556</b>	<b>0.0678</b>	<b>1.5900e-003</b>	<b>0.0694</b>		<b>252.1637</b>	<b>252.1637</b>	<b>7.5500e-003</b>	<b>0.0125</b>	<b>256.0620</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.5 Paving - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.5904	5.2297	7.0314	0.0113		0.2429	0.2429		0.2269	0.2269		1,036.2393	1,036.2393	0.3019		1,043.7858
Paving	0.0000					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
<b>Total</b>	<b>0.5904</b>	<b>5.2297</b>	<b>7.0314</b>	<b>0.0113</b>		<b>0.2429</b>	<b>0.2429</b>		<b>0.2269</b>	<b>0.2269</b>		<b>1,036.2393</b>	<b>1,036.2393</b>	<b>0.3019</b>		<b>1,043.7858</b>

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0476	0.0291	0.5115	1.6400e-003	0.2012	9.7000e-004	0.2022	0.0534	9.0000e-004	0.0543		166.1553	166.1553	3.4200e-003	3.4700e-003	167.2740
<b>Total</b>	<b>0.0476</b>	<b>0.0291</b>	<b>0.5115</b>	<b>1.6400e-003</b>	<b>0.2012</b>	<b>9.7000e-004</b>	<b>0.2022</b>	<b>0.0534</b>	<b>9.0000e-004</b>	<b>0.0543</b>		<b>166.1553</b>	<b>166.1553</b>	<b>3.4200e-003</b>	<b>3.4700e-003</b>	<b>167.2740</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.5 Paving - 2024**

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Off-Road	0.5904	5.2297	7.0314	0.0113		0.2429	0.2429		0.2269	0.2269	0.0000	1,036.239 3	1,036.239 3	0.3019		1,043.785 8
Paving	0.0000					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
<b>Total</b>	<b>0.5904</b>	<b>5.2297</b>	<b>7.0314</b>	<b>0.0113</b>		<b>0.2429</b>	<b>0.2429</b>		<b>0.2269</b>	<b>0.2269</b>	<b>0.0000</b>	<b>1,036.239 3</b>	<b>1,036.239 3</b>	<b>0.3019</b>		<b>1,043.785 8</b>

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0476	0.0291	0.5115	1.6400e-003	0.2012	9.7000e-004	0.2022	0.0534	9.0000e-004	0.0543		166.1553	166.1553	3.4200e-003	3.4700e-003	167.2740
<b>Total</b>	<b>0.0476</b>	<b>0.0291</b>	<b>0.5115</b>	<b>1.6400e-003</b>	<b>0.2012</b>	<b>9.7000e-004</b>	<b>0.2022</b>	<b>0.0534</b>	<b>9.0000e-004</b>	<b>0.0543</b>		<b>166.1553</b>	<b>166.1553</b>	<b>3.4200e-003</b>	<b>3.4700e-003</b>	<b>167.2740</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.6 Architectural Coating - 2024**

**Unmitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	16.8950					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.1808	1.2188	1.8101	2.9700e-003		0.0609	0.0609		0.0609	0.0609		281.4481	281.4481	0.0159		281.8443
<b>Total</b>	<b>17.0758</b>	<b>1.2188</b>	<b>1.8101</b>	<b>2.9700e-003</b>		<b>0.0609</b>	<b>0.0609</b>		<b>0.0609</b>	<b>0.0609</b>		<b>281.4481</b>	<b>281.4481</b>	<b>0.0159</b>		<b>281.8443</b>

**Unmitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0106	6.4700e-003	0.1137	3.7000e-004	0.0447	2.2000e-004	0.0449	0.0119	2.0000e-004	0.0121		36.9234	36.9234	7.6000e-004	7.7000e-004	37.1720
<b>Total</b>	<b>0.0106</b>	<b>6.4700e-003</b>	<b>0.1137</b>	<b>3.7000e-004</b>	<b>0.0447</b>	<b>2.2000e-004</b>	<b>0.0449</b>	<b>0.0119</b>	<b>2.0000e-004</b>	<b>0.0121</b>		<b>36.9234</b>	<b>36.9234</b>	<b>7.6000e-004</b>	<b>7.7000e-004</b>	<b>37.1720</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**3.6 Architectural Coating - 2024**

**Mitigated Construction On-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Archit. Coating	16.8950					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Off-Road	0.1808	1.2188	1.8101	2.9700e-003		0.0609	0.0609		0.0609	0.0609	0.0000	281.4481	281.4481	0.0159		281.8443
<b>Total</b>	<b>17.0758</b>	<b>1.2188</b>	<b>1.8101</b>	<b>2.9700e-003</b>		<b>0.0609</b>	<b>0.0609</b>		<b>0.0609</b>	<b>0.0609</b>	<b>0.0000</b>	<b>281.4481</b>	<b>281.4481</b>	<b>0.0159</b>		<b>281.8443</b>

**Mitigated Construction Off-Site**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Hauling	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Vendor	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000		0.0000	0.0000	0.0000	0.0000	0.0000
Worker	0.0106	6.4700e-003	0.1137	3.7000e-004	0.0447	2.2000e-004	0.0449	0.0119	2.0000e-004	0.0121		36.9234	36.9234	7.6000e-004	7.7000e-004	37.1720
<b>Total</b>	<b>0.0106</b>	<b>6.4700e-003</b>	<b>0.1137</b>	<b>3.7000e-004</b>	<b>0.0447</b>	<b>2.2000e-004</b>	<b>0.0449</b>	<b>0.0119</b>	<b>2.0000e-004</b>	<b>0.0121</b>		<b>36.9234</b>	<b>36.9234</b>	<b>7.6000e-004</b>	<b>7.7000e-004</b>	<b>37.1720</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**4.0 Operational Detail - Mobile**

**4.1 Mitigation Measures Mobile**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Mitigated	0.2546	0.2587	2.5796	6.1900e-003	0.6765	4.1200e-003	0.6807	0.1803	3.8300e-003	0.1842		629.9123	629.9123	0.0362	0.0245	638.1164
Unmitigated	0.2546	0.2587	2.5796	6.1900e-003	0.6765	4.1200e-003	0.6807	0.1803	3.8300e-003	0.1842		629.9123	629.9123	0.0362	0.0245	638.1164

**4.2 Trip Summary Information**

Land Use	Average Daily Trip Rate			Unmitigated	Mitigated
	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Retirement Community	93.96	93.96	93.96	321,076	321,076
Total	93.96	93.96	93.96	321,076	321,076

**4.3 Trip Type Information**

Land Use	Miles			Trip %			Trip Purpose %		
	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW	Primary	Diverted	Pass-by
Retirement Community	14.70	5.90	8.70	40.20	19.20	40.60	86	11	3

**4.4 Fleet Mix**

Land Use	LDA	LDT1	LDT2	MDV	LHD1	LHD2	MHD	HHD	OBUS	UBUS	MCY	SBUS	MH
Retirement Community	0.546200	0.059546	0.185910	0.127866	0.024295	0.006605	0.014499	0.004906	0.000657	0.000381	0.024552	0.000713	0.003869

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**5.0 Energy Detail**

Historical Energy Use: N

**5.1 Mitigation Measures Energy**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
NaturalGas Mitigated	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753
NaturalGas Unmitigated	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753

**5.2 Energy by Land Use - NaturalGas**

Unmitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Retirement Community	986.726	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753
<b>Total</b>		<b>0.0106</b>	<b>0.0909</b>	<b>0.0387</b>	<b>5.8000e-004</b>		<b>7.3500e-003</b>	<b>7.3500e-003</b>		<b>7.3500e-003</b>	<b>7.3500e-003</b>		<b>116.0854</b>	<b>116.0854</b>	<b>2.2200e-003</b>	<b>2.1300e-003</b>	<b>116.7753</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**5.2 Energy by Land Use - Natural Gas**

Mitigated

	Natural Gas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU/yr	lb/day										lb/day					
Retirement Community	0.986726	0.0106	0.0909	0.0387	5.8000e-004		7.3500e-003	7.3500e-003		7.3500e-003	7.3500e-003		116.0854	116.0854	2.2200e-003	2.1300e-003	116.7753
<b>Total</b>		<b>0.0106</b>	<b>0.0909</b>	<b>0.0387</b>	<b>5.8000e-004</b>		<b>7.3500e-003</b>	<b>7.3500e-003</b>		<b>7.3500e-003</b>	<b>7.3500e-003</b>		<b>116.0854</b>	<b>116.0854</b>	<b>2.2200e-003</b>	<b>2.1300e-003</b>	<b>116.7753</b>

**6.0 Area Detail**

**6.1 Mitigation Measures Area**

Use only Natural Gas Hearths

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	lb/day										lb/day					
Mitigated	0.4130	0.4605	2.5758	2.8900e-003		0.0483	0.0483		0.0483	0.0483	0.0000	557.0139	557.0139	0.0147	0.0101	560.4017
Unmitigated	7.9614	0.6293	17.1395	0.0378		2.2285	2.2285		2.2285	2.2285	271.6406	526.3080	797.9487	0.8142	0.0184	823.7984

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**6.2 Area by SubCategory**

**Unmitigated**

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	lb/day										lb/day					
Architectural Coating	0.0231					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Consumer Products	0.2673					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Hearth	7.5990	0.6017	14.7480	0.0376		2.2153	2.2153		2.2153	2.2153	271.6406	522.0000	793.6406	0.8101	0.0184	819.3870
Landscaping	0.0719	0.0276	2.3915	1.3000e-004		0.0133	0.0133		0.0133	0.0133		4.3080	4.3080	4.1300e-003		4.4114
<b>Total</b>	<b>7.9614</b>	<b>0.6293</b>	<b>17.1395</b>	<b>0.0378</b>		<b>2.2285</b>	<b>2.2285</b>		<b>2.2285</b>	<b>2.2285</b>	<b>271.6406</b>	<b>526.3080</b>	<b>797.9487</b>	<b>0.8142</b>	<b>0.0184</b>	<b>823.7983</b>

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**6.2 Area by SubCategory**

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory	lb/day										lb/day					
Architectural Coating	0.0231					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Consumer Products	0.2673					0.0000	0.0000		0.0000	0.0000			0.0000			0.0000
Hearth	0.0507	0.4330	0.1842	2.7600e-003		0.0350	0.0350		0.0350	0.0350	0.0000	552.7059	552.7059	0.0106	0.0101	555.9903
Landscaping	0.0719	0.0276	2.3915	1.3000e-004		0.0133	0.0133		0.0133	0.0133		4.3080	4.3080	4.1300e-003		4.4114
<b>Total</b>	<b>0.4130</b>	<b>0.4605</b>	<b>2.5758</b>	<b>2.8900e-003</b>		<b>0.0483</b>	<b>0.0483</b>		<b>0.0483</b>	<b>0.0483</b>	<b>0.0000</b>	<b>557.0139</b>	<b>557.0139</b>	<b>0.0147</b>	<b>0.0101</b>	<b>560.4017</b>

**7.0 Water Detail**

**7.1 Mitigation Measures Water**

Guadalupe Manor - Orange County, Summer

**EMFAC Off-Model Adjustment Factors for Gasoline Light Duty Vehicle to Account for the SAFE Vehicle Rule Not Applied**

**8.0 Waste Detail**

---

**8.1 Mitigation Measures Waste**

**9.0 Operational Offroad**

---

Equipment Type	Number	Hours/Day	Days/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	-----------	-------------	-------------	-----------

**10.0 Stationary Equipment**

---

**Fire Pumps and Emergency Generators**

Equipment Type	Number	Hours/Day	Hours/Year	Horse Power	Load Factor	Fuel Type
----------------	--------	-----------	------------	-------------	-------------	-----------

**Boilers**

Equipment Type	Number	Heat Input/Day	Heat Input/Year	Boiler Rating	Fuel Type
----------------	--------	----------------	-----------------	---------------	-----------

**User Defined Equipment**

Equipment Type	Number
----------------	--------

**11.0 Vegetation**

---

**AIR QUALITY and GHG IMPACT ANALYSES**  
**GUADALUPE MANOR (17103 MAGNOLIA) RESIDENTIAL PROJECT**  
**FOUNTAIN VALLEY, CALIFORNIA**

Prepared by:

Sara Friedman-Gerrick  
Gerrick Environmental

Prepared for:

Phil Martin & Associates  
Attn: Phil Martin  
2987 NW Fairway Heights Drive  
Bend, Oregon 97703

Date:

May 14, 2023

Project No.: P23-025 A

## **BACKGROUND**

The project site is currently developed with a three-story affordable senior housing facility containing 71 dwelling units. The proposed project involves expansion/addition of a new two-story building to provide 29 additional dwelling units, encompassing 13,498 sf. Vehicular access is proposed to remain via the existing full access driveway at Magnolia Street. There will be 68 parking spaces provided for the new building.

## **ATMOSPHERIC SETTING**

The climate of Fountain Valley, technically called a Mediterranean-type climate, is characterized by warm summers, mild winters, infrequent rainfall, moderate afternoon breezes, and generally fair weather. Temperatures near the project area average a very comfortable 63°F year-round. Summer afternoons are typically in the middle 80s and winter mornings drop to the low- to mid-40s. About 45 summer days reach 90 degrees F, and five days per year may drop to 32 degrees, but significant extremes of temperature are rare in the project area. Rainfall in the Los Angeles Basin varies considerably in both time and space. Rainfall amounts vary from an average of 10 to 18 inches as a function of local exposure and topography. Fountain Valley averages 14.6 inches of rain during a normal year. Almost all the annual rainfall comes from the fringes of mid-latitude storms from late November to early April with summers often completely dry. Light rain (0.1" in 24 hours) falls on 20 days during a normal year with 10 days in the moderate (0.5" in 24 hours category).

Winds blow primarily from southwest to northeast by day and from northeast to the southwest at night in response to the regional pattern of onshore flow by day and offshore flow at night. Average wind speeds are 5 mph average in the Fountain Valley area, reaching 6-8 mph in the afternoon but dropping to near calm conditions (1-3 mph) at night.

The net effect of local airflow in terms of air pollution is that daytime ventilation is good and any locally generated air pollutants will be rapidly dispersed by the strong daytime turbulence. At night, however, pooling of cool air in low elevations combined with light winds does allow for air stagnation in protected areas, especially near area freeways with elevated pollution levels. Because such effects are highly localized, however, the project area is sufficiently far from any major roadways such that it will be little affected by such air stagnation effects.

In addition to winds that control the rate and direction of pollution dispersal, Southern California is notorious for strong temperature inversions that limit the vertical depth through which pollution can be mixed. In summer, coastal areas are characterized by a sharp discontinuity between the cool marine air at the surface and the warm, sinking air aloft within the high-pressure cell over the ocean to the west. This marine/subsidence inversion allows for good local mixing, but acts like a giant lid over the basin. Air starting onshore at the beach is relatively clean, but becomes progressively more polluted as sources continue to add pollution from below without any dilution from above. Air arriving at Fountain Valley during warm season marine flow conditions has undergone limited photochemical reactions, but not to its fullest extent possible. Summer smog

levels in Fountain Valley are much lower than in inland valleys of the basin such as the San Gabriel or the Pomona-Walnut Valleys. Summer air quality is only moderately degraded compared to the severe degradation found farther inland within the air basin.

A second inversion type forms on clear, winter nights when cold air off the mountains sinks to the surface while the air aloft remains warm. This process forms radiation inversions. These inversions, in conjunction with calm winds, trap pollutants such as automobile exhaust near their source. During the long nocturnal drainage flow from land to sea, the exhaust pollutants continually accumulate within the shallow, cool layer of air near the ground. Central Orange County thus may experience elevated levels of carbon monoxide and nitrogen oxides because of this winter inversion condition. With ongoing vehicular improvements, clean air standards are generally not exceeded during nocturnal stagnation periods as they were 10-20 years ago.

Both types of inversions occur throughout the year to some extent, but the marine inversions are very dominant during the day in summer, and radiation inversions are much stronger on winter nights when nights are long, and air is cool. The governing role of these inversions in atmospheric dispersion leads to a substantially different air quality environment in summer near the project area than in winter.

# AIR QUALITY SETTING

## AMBIENT AIR QUALITY STANDARDS (AAQS)

In order to gauge the significance of the air quality impacts of the proposed project, those impacts, together with existing background air quality levels, must be compared to the applicable ambient air quality standards. These standards are the levels of air quality considered safe, with an adequate margin of safety, to protect public health and welfare. They are designed to protect those people most susceptible to further respiratory distress such as asthmatics, the elderly, very young children, people already weakened by other disease or illness, and persons engaged in strenuous work or exercise, called "sensitive receptors." Healthy adults can tolerate occasional exposure to air pollutant concentrations considerably above these minimum standards before adverse effects are observed. Recent research has shown, however, that chronic exposure to ozone (the primary ingredient in photochemical smog) may lead to adverse respiratory health even at concentrations close to the ambient standard.

National AAQS were established in 1971 for six pollution species with states retaining the option to add other pollutants, require more stringent compliance, or to include different exposure periods. The initial attainment deadline of 1977 was extended several times in air quality problem areas like Southern California. In 2003, the Environmental Protection Agency (EPA) adopted a rule, which extended and established a new attainment deadline for ozone for the year 2021. Because the State of California had established AAQS several years before the federal action and because of unique air quality problems introduced by the restrictive dispersion meteorology, there is considerable difference between state and national clean air standards. Those standards currently in effect in California are shown in Table 1. Sources and health effects of various pollutants are shown in Table 2.

The Federal Clean Air Act Amendments (CAAA) of 1990 required that the U.S. Environmental Protection Agency (EPA) review all national AAQS in light of currently known health effects. EPA was charged with modifying existing standards or promulgating new ones where appropriate. EPA subsequently developed standards for chronic ozone exposure (8+ hours per day) and for very small diameter particulate matter (called "PM-2.5"). New national AAQS were adopted in 1997 for these pollutants.

Planning and enforcement of the federal standards for PM-2.5 and for ozone (8-hour) were challenged by trucking and manufacturing organizations. In a unanimous decision, the U.S. Supreme Court ruled that EPA did not require specific congressional authorization to adopt national clean air standards. The Court also ruled that health-based standards did not require preparation of a cost-benefit analysis. The Court did find, however, that there was some inconsistency between existing and "new" standards in their required attainment schedules. Such attainment-planning schedule inconsistencies centered mainly on the 8-hour ozone standard. EPA subsequently agreed to downgrade the attainment designation for a large number of communities to "non-attainment" for the 8-hour ozone standard.

**Table 1**

<b>Ambient Air Quality Standards</b>						
Pollutant	Averaging Time	California Standards <sup>1</sup>		National Standards <sup>2</sup>		
		Concentration <sup>3</sup>	Method <sup>4</sup>	Primary <sup>3,5</sup>	Secondary <sup>3,6</sup>	Method <sup>7</sup>
Ozone (O <sub>3</sub> ) <sup>8</sup>	1 Hour	0.09 ppm (180 µg/m <sup>3</sup> )	Ultraviolet Photometry	—	Same as Primary Standard	Ultraviolet Photometry
	8 Hour	0.070 ppm (137 µg/m <sup>3</sup> )		0.070 ppm (137 µg/m <sup>3</sup> )		
Respirable Particulate Matter (PM <sub>10</sub> ) <sup>9</sup>	24 Hour	50 µg/m <sup>3</sup>	Gravimetric or Beta Attenuation	150 µg/m <sup>3</sup>	Same as Primary Standard	Inertial Separation and Gravimetric Analysis
	Annual Arithmetic Mean	20 µg/m <sup>3</sup>		—		
Fine Particulate Matter (PM <sub>2.5</sub> ) <sup>9</sup>	24 Hour	—	—	35 µg/m <sup>3</sup>	Same as Primary Standard	Inertial Separation and Gravimetric Analysis
	Annual Arithmetic Mean	12 µg/m <sup>3</sup>	Gravimetric or Beta Attenuation	12.0 µg/m <sup>3</sup>	15 µg/m <sup>3</sup>	
Carbon Monoxide (CO)	1 Hour	20 ppm (23 mg/m <sup>3</sup> )	Non-Dispersive Infrared Photometry (NDIR)	35 ppm (40 mg/m <sup>3</sup> )	—	Non-Dispersive Infrared Photometry (NDIR)
	8 Hour	9.0 ppm (10 mg/m <sup>3</sup> )		9 ppm (10 mg/m <sup>3</sup> )	—	
	8 Hour (Lake Tahoe)	6 ppm (7 mg/m <sup>3</sup> )		—	—	
Nitrogen Dioxide (NO <sub>2</sub> ) <sup>10</sup>	1 Hour	0.18 ppm (339 µg/m <sup>3</sup> )	Gas Phase Chemiluminescence	100 ppb (188 µg/m <sup>3</sup> )	—	Gas Phase Chemiluminescence
	Annual Arithmetic Mean	0.030 ppm (57 µg/m <sup>3</sup> )		0.053 ppm (100 µg/m <sup>3</sup> )	Same as Primary Standard	
Sulfur Dioxide (SO <sub>2</sub> ) <sup>11</sup>	1 Hour	0.25 ppm (655 µg/m <sup>3</sup> )	Ultraviolet Fluorescence	75 ppb (196 µg/m <sup>3</sup> )	—	Ultraviolet Fluorescence; Spectrophotometry (Pararosaniline Method)
	3 Hour	—		—	0.5 ppm (1300 µg/m <sup>3</sup> )	
	24 Hour	0.04 ppm (105 µg/m <sup>3</sup> )		0.14 ppm (for certain areas) <sup>11</sup>	—	
	Annual Arithmetic Mean	—		0.030 ppm (for certain areas) <sup>11</sup>	—	
Lead <sup>12,13</sup>	30 Day Average	1.5 µg/m <sup>3</sup>	Atomic Absorption	—	—	High Volume Sampler and Atomic Absorption
	Calendar Quarter	—		1.5 µg/m <sup>3</sup> (for certain areas) <sup>12</sup>	Same as Primary Standard	
	Rolling 3-Month Average	—		0.15 µg/m <sup>3</sup>		
Visibility Reducing Particles <sup>14</sup>	8 Hour	See footnote 14	Beta Attenuation and Transmittance through Filter Tape	<b>No National Standards</b>		
Sulfates	24 Hour	25 µg/m <sup>3</sup>	Ion Chromatography			
Hydrogen Sulfide	1 Hour	0.03 ppm (42 µg/m <sup>3</sup> )	Ultraviolet Fluorescence			
Vinyl Chloride <sup>12</sup>	24 Hour	0.01 ppm (26 µg/m <sup>3</sup> )	Gas Chromatography			

See footnotes on next page ...

For more information please call ARB-PIO at (916) 322-2990

California Air Resources Board (5/4/16)

## Table 1 (continued)

1. California standards for ozone, carbon monoxide (except 8-hour Lake Tahoe), sulfur dioxide (1 and 24 hour), nitrogen dioxide, and particulate matter (PM10, PM2.5, and visibility reducing particles), are values that are not to be exceeded. All others are not to be equaled or exceeded. California ambient air quality standards are listed in the Table of Standards in Section 70200 of Title 17 of the California Code of Regulations.
2. National standards (other than ozone, particulate matter, and those based on annual arithmetic mean) are not to be exceeded more than once a year. The ozone standard is attained when the fourth highest 8-hour concentration measured at each site in a year, averaged over three years, is equal to or less than the standard. For PM10, the 24 hour standard is attained when the expected number of days per calendar year with a 24-hour average concentration above  $150 \mu\text{g}/\text{m}^3$  is equal to or less than one. For PM2.5, the 24 hour standard is attained when 98 percent of the daily concentrations, averaged over three years, are equal to or less than the standard. Contact the U.S. EPA for further clarification and current national policies.
3. Concentration expressed first in units in which it was promulgated. Equivalent units given in parentheses are based upon a reference temperature of  $25^\circ\text{C}$  and a reference pressure of 760 torr. Most measurements of air quality are to be corrected to a reference temperature of  $25^\circ\text{C}$  and a reference pressure of 760 torr; ppm in this table refers to ppm by volume, or micromoles of pollutant per mole of gas.
4. Any equivalent measurement method which can be shown to the satisfaction of the ARB to give equivalent results at or near the level of the air quality standard may be used.
5. National Primary Standards: The levels of air quality necessary, with an adequate margin of safety to protect the public health.
6. National Secondary Standards: The levels of air quality necessary to protect the public welfare from any known or anticipated adverse effects of a pollutant.
7. Reference method as described by the U.S. EPA. An "equivalent method" of measurement may be used but must have a "consistent relationship to the reference method" and must be approved by the U.S. EPA.
8. On October 1, 2015, the national 8-hour ozone primary and secondary standards were lowered from 0.075 to 0.070 ppm.
9. On December 14, 2012, the national annual PM2.5 primary standard was lowered from  $15 \mu\text{g}/\text{m}^3$  to  $12.0 \mu\text{g}/\text{m}^3$ . The existing national 24-hour PM2.5 standards (primary and secondary) were retained at  $35 \mu\text{g}/\text{m}^3$ , as was the annual secondary standard of  $15 \mu\text{g}/\text{m}^3$ . The existing 24-hour PM10 standards (primary and secondary) of  $150 \mu\text{g}/\text{m}^3$  also were retained. The form of the annual primary and secondary standards is the annual mean, averaged over 3 years.
10. To attain the 1-hour national standard, the 3-year average of the annual 98th percentile of the 1-hour daily maximum concentrations at each site must not exceed 100 ppb. Note that the national 1-hour standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the national 1-hour standard to the California standards the units can be converted from ppb to ppm. In this case, the national standard of 100 ppb is identical to 0.100 ppm.
11. On June 2, 2010, a new 1-hour  $\text{SO}_2$  standard was established and the existing 24-hour and annual primary standards were revoked. To attain the 1-hour national standard, the 3-year average of the annual 99th percentile of the 1-hour daily maximum concentrations at each site must not exceed 75 ppb. The 1971  $\text{SO}_2$  national standards (24-hour and annual) remain in effect until one year after an area is designated for the 2010 standard, except that in areas designated nonattainment for the 1971 standards, the 1971 standards remain in effect until implementation plans to attain or maintain the 2010 standards are approved.  
Note that the 1-hour national standard is in units of parts per billion (ppb). California standards are in units of parts per million (ppm). To directly compare the 1-hour national standard to the California standard the units can be converted to ppm. In this case, the national standard of 75 ppb is identical to 0.075 ppm.
12. The ARB has identified lead and vinyl chloride as 'toxic air contaminants' with no threshold level of exposure for adverse health effects determined. These actions allow for the implementation of control measures at levels below the ambient concentrations specified for these pollutants.
13. The national standard for lead was revised on October 15, 2008 to a rolling 3-month average. The 1978 lead standard ( $1.5 \mu\text{g}/\text{m}^3$  as a quarterly average) remains in effect until one year after an area is designated for the 2008 standard, except that in areas designated nonattainment for the 1978 standard, the 1978 standard remains in effect until implementation plans to attain or maintain the 2008 standard are approved.
14. In 1989, the ARB converted both the general statewide 10-mile visibility standard and the Lake Tahoe 30-mile visibility standard to instrumental equivalents, which are "extinction of 0.23 per kilometer" and "extinction of 0.07 per kilometer" for the statewide and Lake Tahoe Air Basin standards, respectively.

For more information please call ARB-PIO at (916) 322-2990

California Air Resources Board (5/4/16)

**Table 2  
Health Effects of Major Criteria Pollutants**

<b>Pollutants</b>	<b>Sources</b>	<b>Primary Effects</b>
Carbon Monoxide (CO)	<ul style="list-style-type: none"> <li>• Incomplete combustion of fuels and other carbon-containing substances, such as motor exhaust.</li> <li>• Natural events, such as decomposition of organic matter.</li> </ul>	<ul style="list-style-type: none"> <li>• Reduced tolerance for exercise.</li> <li>• Impairment of mental function.</li> <li>• Impairment of fetal development.</li> <li>• Death at high levels of exposure.</li> <li>• Aggravation of some heart diseases (angina).</li> </ul>
Nitrogen Dioxide (NO <sub>2</sub> )	<ul style="list-style-type: none"> <li>• Motor vehicle exhaust.</li> <li>• High temperature stationary combustion.</li> <li>• Atmospheric reactions.</li> </ul>	<ul style="list-style-type: none"> <li>• Aggravation of respiratory illness.</li> <li>• Reduced visibility.</li> <li>• Reduced plant growth.</li> <li>• Formation of acid rain.</li> </ul>
Ozone (O <sub>3</sub> )	<ul style="list-style-type: none"> <li>• Atmospheric reaction of organic gases with nitrogen oxides in sunlight.</li> </ul>	<ul style="list-style-type: none"> <li>• Aggravation of respiratory and cardiovascular diseases.</li> <li>• Irritation of eyes.</li> <li>• Impairment of cardiopulmonary function.</li> <li>• Plant leaf injury.</li> </ul>
Lead (Pb)	<ul style="list-style-type: none"> <li>• Contaminated soil.</li> </ul>	<ul style="list-style-type: none"> <li>• Impairment of blood function and nerve construction.</li> <li>• Behavioral and hearing problems in children.</li> </ul>
Respirable Particulate Matter (PM-10)	<ul style="list-style-type: none"> <li>• Stationary combustion of solid fuels.</li> <li>• Construction activities.</li> <li>• Industrial processes.</li> <li>• Atmospheric chemical reactions.</li> </ul>	<ul style="list-style-type: none"> <li>• Reduced lung function.</li> <li>• Aggravation of the effects of gaseous pollutants.</li> <li>• Aggravation of respiratory and cardio respiratory diseases.</li> <li>• Increased cough and chest discomfort.</li> <li>• Soiling.</li> <li>• Reduced visibility.</li> </ul>
Fine Particulate Matter (PM-2.5)	<ul style="list-style-type: none"> <li>• Fuel combustion in motor vehicles, equipment, and industrial sources.</li> <li>• Residential and agricultural burning.</li> <li>• Industrial processes.</li> <li>• Also, formed from photochemical reactions of other pollutants, including NO<sub>x</sub>, sulfur oxides, and organics.</li> </ul>	<ul style="list-style-type: none"> <li>• Increases respiratory disease.</li> <li>• Lung damage.</li> <li>• Cancer and premature death.</li> <li>• Reduces visibility and results in surface soiling.</li> </ul>
Sulfur Dioxide (SO <sub>2</sub> )	<ul style="list-style-type: none"> <li>• Combustion of sulfur-containing fossil fuels.</li> <li>• Smelting of sulfur-bearing metal ores.</li> <li>• Industrial processes.</li> </ul>	<ul style="list-style-type: none"> <li>• Aggravation of respiratory diseases (asthma, emphysema).</li> <li>• Reduced lung function.</li> <li>• Irritation of eyes.</li> <li>• Reduced visibility.</li> <li>• Plant injury.</li> <li>• Deterioration of metals, textiles, leather, finishes, coatings, etc.</li> </ul>

Source: California Air Resources Board, 2002.

Evaluation of the most current data on the health effects of inhalation of fine particulate matter prompted the California Air Resources Board (ARB) to recommend adoption of the statewide PM-2.5 standard that is more stringent than the federal standard. This standard was adopted in 2002. The State PM-2.5 standard is more of a goal in that it does not have specific attainment planning requirements like a federal clean air standard, but only requires continued progress towards attainment.

Similarly, the ARB extensively evaluated health effects of ozone exposure. A new state standard for an 8-hour ozone exposure was adopted in 2005, which aligned with the exposure period for the federal 8-hour standard. The California 8-hour ozone standard of 0.07 ppm is more stringent than the federal 8-hour standard of 0.075 ppm. The state standard, however, does not have a specific attainment deadline. California air quality jurisdictions are required to make steady progress towards attaining state standards, but there are no hard deadlines or any consequences of non-attainment. During the same re-evaluation process, the ARB adopted an annual state standard for nitrogen dioxide (NO<sub>2</sub>) that is more stringent than the corresponding federal standard, and strengthened the state one-hour NO<sub>2</sub> standard.

As part of EPA's 2002 consent decree on clean air standards, a further review of airborne particulate matter (PM) and human health was initiated. A substantial modification of federal clean air standards for PM was promulgated in 2006. Standards for PM-2.5 were strengthened, a new class of PM in the 2.5 to 10 micron size was created, some PM-10 standards were revoked, and a distinction between rural and urban air quality was adopted. In December, 2012, the federal annual standard for PM-2.5 was reduced from 15 µg/m<sup>3</sup> to 12 µg/m<sup>3</sup> which matches the California AAQS. The severity of the basin's non-attainment status for PM-2.5 may be increased by this action and thus require accelerated planning for future PM-2.5 attainment.

In response to continuing evidence that ozone exposure at levels just meeting federal clean air standards is demonstrably unhealthful, EPA had proposed a further strengthening of the 8-hour standard. A new 8-hour ozone standard was adopted in 2015 after extensive analysis and public input. The adopted national 8-hour ozone standard is 0.07 ppm which matches the current California standard. It will require three years of ambient data collection, then 2 years of non-attainment findings and planning protocol adoption, then several years of plan development and approval. Final air quality plans for the new standard are likely to be adopted around 2022. Ultimate attainment of the new standard in ozone problem areas such as Southern California might be after 2025.

In 2010 a new federal one-hour primary standard for nitrogen dioxide (NO<sub>2</sub>) was adopted. This standard is more stringent than the existing state standard. Based upon air quality monitoring data in the South Coast Air Basin, the California Air Resources Board has requested the EPA to designate the basin as being in attainment for this standard. The federal standard for sulfur dioxide (SO<sub>2</sub>) was also recently revised. However, with minimal combustion of coal and mandatory use of low sulfur fuels in California, SO<sub>2</sub> is typically not a problem pollutant.

## BASELINE AIR QUALITY

Existing and probable future levels of air quality around the project area can best be best inferred from ambient air quality measurements conducted by the SCAQMD at the Anaheim monitoring station. This station measures both regional pollution levels such as smog, as well as primary vehicular pollution levels near busy roadways such as nitrogen oxides. Pollutants such as particulates (PM-10 and PM-2.5) are also monitored at Anaheim. Table 3 is a 4-year summary of the most recent monitoring data for the major air pollutants compiled from the Anaheim air monitoring station. From this data the following conclusions regarding air quality trends can be drawn.

Photochemical smog (ozone) levels rarely occasionally exceed standards. All state and federal ozone standards have exceeded less than one percent of all days in the past four years. Measurements from more recent years demonstrate progressively improved ozone levels in the area. Measurements for the most recent year, 2021, show no violations.

Respirable dust (PM-10) levels occasionally exceed the state standard on approximately three percent of all days. The less stringent federal PM-10 standard has not been exceeded in the last four years.

The federal ultra-fine particulate (PM-2.5) standard of  $35 \mu\text{g}/\text{m}^3$  has been exceeded on approximately one percent of measurement days in the last four years.

More localized pollutants such as carbon monoxide, nitrogen oxides, etc. are very low near the project site. There is substantial excess dispersive capacity to accommodate localized vehicular air pollutants such as NO<sub>x</sub> or CO without any threat of violating applicable AAQS.

Although complete attainment of every clean air standard is not yet imminent, extrapolation of the steady improvement trend suggests that such attainment could occur within the reasonably near future.

**Table 3**  
**Air Quality Monitoring Summary (2018-2021)**  
**(Number of Days Standards Were Exceeded, and**  
**Maximum Levels During Such Violations)**

Pollutant/Standard	2018	2019	2020	2021
<b>Ozone</b>				
1-Hour > 0.09 ppm (S)	1	1	6	0
8-Hour > 0.07 ppm (S)	1	1	15	0
8- Hour > 0.075 ppm (F)	0	1	4	0
Max. 1-Hour Conc. (ppm)	0.112	0.096	0.142	0.103
Max. 8-Hour Conc. (ppm)	0.071	0.082	0.097	0.068
<b>Carbon Monoxide</b>				
8- Hour > 9. ppm (S,F)	0	0	0	0
Max 8-hour Conc. (ppm)	1.9	1.3	1.7	1.5
<b>Nitrogen Dioxide</b>				
1-Hour > 0.18 ppm (S)	0	0	0	0
Max. 1-Hour Conc. (ppm)	0.066	0.059	0.071	0.067
<b>Inhalable Particulates (PM-10)</b>				
24-hour > 50 µg/m <sup>3</sup> (S)	13/320	13/364	13/329	12/361
24-hour > 150 µg/m <sup>3</sup> (F)	0/320	0/364	0/329	0/361
Max. 24-Hr. Conc. (µg/m <sup>3</sup> )	129.	127.	120.	115.
<b>Ultra-Fine Particulates (PM-2.5)</b>				
24-Hour > 35 µg/m <sup>3</sup> (F)	3/353	3/346	1/355	9/364
Max. 24-Hr. Conc. (µg/m <sup>3</sup> )	54.1	36.1	41.4	54.4

S=State Standard  
F=Federal Standard

Source: South Coast AQMD Air Monitoring Station Data Summary, Anaheim Station (3176)

## AIR QUALITY PLANNING

The Federal Clean Air Act (1977 Amendments) required that designated agencies in any area of the nation not meeting national clean air standards must prepare a plan demonstrating the steps that would bring the area into compliance with all national standards. The SCAB could not meet the deadlines for ozone, nitrogen dioxide, carbon monoxide, or PM-10. In the SCAB, the agencies designated by the governor to develop regional air quality plans are the SCAQMD and the Southern California Association of Governments (SCAG). The two agencies first adopted an Air Quality Management Plan (AQMP) in 1979 and revised it several times as earlier attainment forecasts were shown to be overly optimistic.

The 1990 Federal Clean Air Act Amendment (CAAA) required that all states with air-sheds with “serious” or worse ozone problems submit a revision to the State Implementation Plan (SIP). Substantial reductions in emissions of ROG, NO<sub>x</sub> and CO are forecast to continue throughout the next several decades. Unless new particulate control programs are implemented, PM-10 and PM-2.5 are forecast to slightly increase.

The Air Quality Management District (AQMD) adopted an updated clean air “blueprint” in August 2003. The 2003 Air Quality Management Plan (AQMP) was approved by the EPA in 2004. The AQMP outlined the air pollution measures needed to meet federal health-based standards for ozone by 2010 and for particulates (PM-10) by 2006. The 2003 AQMP was based upon the federal one-hour ozone standard which was revoked late in 2005 and replaced by an 8-hour federal standard. Because of the revocation of the hourly standard, a new air quality planning cycle was initiated.

With re-designation of the air basin as non-attainment for the 8-hour ozone standard, a new attainment plan was developed. This plan shifted most of the one-hour ozone standard attainment strategies to the 8-hour standard. As previously noted, the attainment date was to “slip” from 2010 to 2021. The updated attainment plan also includes strategies for ultimately meeting the federal PM-2.5 standard.

Because Projected attainment by 2021 required control technologies that did not exist yet, the SCAQMD requested a voluntary “bump-up” from a “severe non-attainment” area to an “extreme non-attainment” designation for ozone. The extreme designation was to allow a longer time period for these technologies to develop. If attainment cannot be demonstrated within the specified deadline without relying on “black-box” measures, EPA would have been required to impose sanctions on the region had the bump-up request not been approved. In April 2010, the EPA approved the change in the non-attainment designation from “severe-17” to “extreme.” This reclassification set a later attainment deadline (2024), but also required the air basin to adopt even more stringent emissions controls.

In other air quality attainment plan reviews, EPA had disapproved part of the SCAB PM-2.5 attainment plan included in the AQMP. EPA stated that the current attainment plan relied on PM-2.5 control regulations that had not yet been approved or implemented. It was expected that several rules that were pending approval would remove the identified deficiencies. If these issues were not resolved within the next several years, federal funding sanctions for transportation projects could

result. The 2012 AQMP included in the current California State Implementation Plan (SIP) was expected to remedy identified PM-2.5 planning deficiencies.

The federal Clean Air Act requires that non-attainment air basins have EPA approved attainment plans in place. This requirement includes the federal one-hour ozone standard even though that standard was revoked almost ten years ago. There was no approved attainment plan for the one-hour federal standard at the time of revocation. Through a legal quirk, the SCAQMD is now required to develop an AQMP for the long since revoked one-hour federal ozone standard. Because the current SIP for the basin contains a number of control measures for the 8-hour ozone standard that are equally effective for one-hour levels, the 2012 AQMP was believed to satisfy hourly attainment planning requirements.

AQMPs are required to be updated at regular intervals. The 2012 AQMP was adopted in early 2013. An updated 2016 AQMP was adopted by the SCAQMD Board in March 2017. The 2016 AQMD demonstrated the emissions reductions shown in Table 4 compared to the 2012 AQMP.

**Table 4  
Comparison of Emissions by Major Source Category From 2012 AQMP**

Pollutant	Stationary Sources	Mobile Sources
VOC	-12%	-3%
NOx	-13%	-1%
SOx	-34%	-23%
PM2.5	-9%	-7%

\*source 2016 AQMP

SCAQMD has initiated the development of the 2022 AQMP to address the attainment of the 2015 8-hour ozone standard (70 ppb) for South Coast Air Basin and Coachella Valley which will focus on attaining the 70 ppb 8-hour ozone National Ambient Air Quality Standard (NAAQS) by 2037. On-road vehicles and off-road mobile sources represent the largest categories of NOx emissions. Accomplishment of attainment goals requires an approximate 70% reduction in NOx emissions. Large scale transition to zero emission technologies is a key strategy. To this end, Governor Executive Order N-79-20 requires 100 percent EV sales by 2035 for automobiles and short haul drayage trucks. A full transition to EV buses and heavy-duty long-haul trucks is required by 2045.

The proposed project does not directly relate to the AQMP in that there are no specific air quality programs or regulations governing residential projects. Conformity with adopted plans, forecasts and programs relative to population, housing, employment and land use is the primary yardstick by which impact significance of planned growth is determined. The SCAQMD, however, while acknowledging that the AQMP is a growth-accommodating document, does not favor designating regional impacts as less-than-significant just because the proposed development is consistent with regional growth projections. Air quality impact significance for the proposed project has therefore been analyzed on a project-specific basis.

# AIR QUALITY IMPACT

## STANDARDS OF SIGNIFICANCE

Air quality impacts are considered “significant” if they cause clean air standards to be violated where they are currently met, or if they “substantially” contribute to an existing violation of standards. Any substantial emissions of air contaminants for which there is no safe exposure, or nuisance emissions such as dust or odors, would also be considered a significant impact.

Appendix G of the California CEQA Guidelines offers the following four tests of air quality impact significance. A project would have a potentially significant impact if it:

- a. Conflicts with or obstructs implementation of the applicable air quality plan.
- b. Results in a cumulatively considerable net increase of any criteria pollutants for which the project region is non-attainment under an applicable federal or state ambient air quality standard.
- c. Exposes sensitive receptors to substantial pollutant concentrations.
- d. Creates objectionable odors affecting a substantial number of people.

## Primary Pollutants

Air quality impacts generally occur on two scales of motion. Near an individual source of emissions or a collection of sources such as a crowded intersection or parking lot, levels of those pollutants that are emitted in their already unhealthful form will be highest. Carbon monoxide (CO) is an example of such a pollutant. Primary pollutant impacts can generally be evaluated directly in comparison to appropriate clean air standards. Violations of these standards where they are currently met, or a measurable worsening of an existing or future violation, would be considered a significant impact. Many particulates, especially fugitive dust emissions, are also primary pollutants. Because of the non-attainment status of the South Coast Air Basin (SCAB) for PM-10, an aggressive dust control program is required to control fugitive dust during project construction.

## Secondary Pollutants

Many pollutants, however, require time to transform from a more benign form to a more unhealthful contaminant. Their impact occurs regionally far from the source. Their incremental regional impact is minute on an individual basis and cannot be quantified except through complex photochemical computer models. Analysis of significance of such emissions is based upon a specified number of emissions (pounds, tons, etc.) even though there is no way to translate those emissions directly into a corresponding ambient air quality impact.

Because of the chemical complexity of primary versus secondary pollutants, the SCAQMD has designated significant emissions levels as surrogates for evaluating regional air quality impact

significance independent of chemical transformation processes. Projects with daily emissions that exceed any of the following emission thresholds are recommended by the SCAQMD to be considered significant under CEQA guidelines.

**Table 5**  
**Daily Emissions Thresholds**

<b>Pollutant</b>	<b>Construction</b>	<b>Operations</b>
ROG	75	55
NOx	100	55
CO	550	550
PM-10	150	150
PM-2.5	55	55
SOx	150	150
Lead	3	3

Source: SCAQMD CEQA Air Quality Handbook, November, 1993 Rev.

## CONSTRUCTION ACTIVITY IMPACTS

CalEEMod was developed by the SCAQMD to provide a model by which to calculate both construction emissions and operational emissions from a variety of land use projects. It calculates both the daily maximum and annual average emissions for criteria pollutants as well as total or annual greenhouse gas (GHG) emissions.

The proposed project involves expansion/addition of a new two-story building to provide 29 additional dwelling units, encompassing 13,498 sf. There will be 68 parking spaces provided for the new building.

Estimated construction emissions were modeled using CalEEMod2020.4.0 to identify maximum daily emissions for each pollutant during project construction. Although there is a newer CalEEMod the SCAQMD website link is to the version used in this report.<sup>1</sup> Construction was modeled in using default construction equipment and schedule for a project of this size as shown in Table 6.

**Table 6  
Construction Activity Equipment Fleet**

<b>Phase Name and Duration</b>	<b>Equipment</b>
Demolition (10 days)	1 Concrete Saw
	1 Dozer
	2 Loader/Backhoes
Grading (4 days)	1 Grader
	1 Dozer
	1 Loader/Backhoe
Construction (100 days)	1 Crane
	2 Loader/Backhoes
	2 Forklifts
Paving (5 days)	1 Paver
	4 Mixers
	1 Loader/Backhoe
	1 Roller

Utilizing the indicated equipment fleet and durations shown in Table 6 the following worst-case daily construction emissions are calculated by CalEEMod and are listed in Table 7.

<sup>1</sup> <https://www.aqmd.gov/home/rules-compliance/ceqa/air-quality-modeling>

**Table 7**  
**Construction Activity Emissions**  
**Maximum Daily Emissions (pounds/day)**

<b>Maximal Construction Emissions</b>	<b>ROG</b>	<b>NOx</b>	<b>CO</b>	<b>SO<sub>2</sub></b>	<b>PM-10</b>	<b>PM-2.5</b>
<b>2024</b>						
Unmitigated	17.1	9.7	7.7	0.0	5.8	3.0
Mitigated	17.1	9.7	7.7	0.0	2.9	1.5
SCAQMD Thresholds	75	100	550	150	150	55

Peak daily construction activity emissions are estimated to be below SCAQMD CEQA thresholds without the need for added mitigation. The only model-based mitigation measure applied for this project was watering exposed dirt surfaces at least two times per day to minimize the generation of fugitive dust generation during the four days of grading.

Construction equipment exhaust contains carcinogenic compounds within the diesel exhaust particulates. The toxicity of diesel exhaust is evaluated relative to a 24-hour per day, 365 days per year, 70-year lifetime exposure. The SCAQMD does not generally require the analysis of construction-related diesel emissions relative to health risk due to the short period for which the majority of diesel exhaust would occur. Health risk analyses are typically assessed over a 9-, 30-, or 70-year timeframe and not over a relatively brief construction period due to the lack of health risk associated with such a brief exposure.

## **LOCALIZED SIGNIFICANCE THRESHOLDS**

The SCAQMD has developed analysis parameters to evaluate ambient air quality on a local level in addition to the more regional emissions-based thresholds of significance. These analysis elements are called Localized Significance Thresholds (LSTs). LSTs were developed in response to Governing Board’s Environmental Justice Enhancement Initiative 1-4 and the LST methodology was provisionally adopted in October 2003 and formally approved by SCAQMD’s Mobile Source Committee in February 2005.

Use of an LST analysis for a project is optional. LSTs are applicable for a sensitive receptor where it is possible that an individual could remain for 24 hours such as a residence, hospital or convalescent facility.

LSTs are only applicable to the following criteria pollutants: oxides of nitrogen (NOx), carbon monoxide (CO), and particulate matter (PM-10 and PM-2.5). LSTs represent the maximum emissions from a project that are not expected to cause or contribute to an exceedance of the most stringent applicable federal or state ambient air quality standard and are developed based on the ambient concentrations of that pollutant for each source receptor area and distance to the nearest sensitive receptor.

LST screening tables are available for 25, 50-, 100-, 200- and 500-meter source-receptor distances. For this project, there are adjacent residences such that the most conservative 25-meter distance was modeled.

The SCAQMD has issued guidance on applying CalEEMod to LSTs. LST pollutant screening level concentration data is currently published for 1-, 2- and 5-acre sites for varying distances. For this project, the most stringent thresholds for a 1-acre site were applied.

The following thresholds and emissions in Table 8 are therefore determined (pounds per day):

**Table 8  
LST and Project Emissions (pounds/day)**

<b>LST 1 acre/25 meters N Coastal Orange County</b>	<b>CO</b>	<b>NOx</b>	<b>PM-10</b>	<b>PM-2.5</b>
<b>LST Thresholds</b>	647	92	4	3
<b>Max On-Site Emissions</b>				
<b>Unmitigated</b>	8	10	6	3
<b>Mitigated</b>	8	10	3	2

CalEEMod Output in Appendix

LSTs were compared to the maximum daily construction activities. As seen in Table 8, with active dust suppression, mitigated emissions meet the LST for construction thresholds. LST impacts are less-than-significant.

Therefore, the following construction mitigation measure is necessary to ensure LST thresholds are maintained below significance thresholds:

- Exposed surfaces will be watered at least two times per day during grading activities.

## **OPERATIONAL IMPACTS**

The proposed project will generate 94 daily trip ends. Operational emissions were calculated for an assumed full occupancy year of 2024. The operational impacts are shown in Table 9.

**Table 9  
Proposed Uses Daily Operational Impacts**

<b>Source</b>	<b>Operational Emissions (lbs/day)</b>					
	<b>ROG</b>	<b>NOx</b>	<b>CO</b>	<b>SO<sub>2</sub></b>	<b>PM-10</b>	<b>PM-2.5</b>
Area*	0.4	0.5	2.6	0.0	0.0	0.0
Energy	0.0	0.1	0.0	0.0	0.0	0.0
Mobile	0.3	0.2	2.6	0.0	0.7	0.2
<b>Total</b>	<b>0.7</b>	<b>0.8</b>	<b>5.2</b>	<b>0.0</b>	<b>0.7</b>	<b>0.2</b>
SCAQMD Threshold	55	55	550	150	150	55
Exceeds Threshold?	No	No	No	No	No	No

\*assumes use of gas hearths if any (not wood burning)

Source: CalEEMod Output in Appendix

As shown, operational emissions will not exceed applicable SCAQMD operational emissions CEQA thresholds of significance.

## **CONSTRUCTION EMISSIONS MINIMIZATION**

Construction activities are not anticipated to cause dust emissions to exceed SCAQMD CEQA thresholds. Nevertheless, emissions minimization through enhanced dust control measures is recommended for use because of the non-attainment status of the air and proximity of sensitive uses. Recommended measures include:

### **Fugitive Dust Control**

- Apply soil stabilizers or moisten inactive areas.
- Water exposed surfaces as needed to avoid visible dust leaving the construction site (typically 2-3 times/day).
- Cover all stock piles with tarps at the end of each day or as needed.
- Provide water spray during loading and unloading of earthen materials.
- Minimize in-out traffic from construction zone
- Cover all trucks hauling dirt, sand, or loose material and require all trucks to maintain at least two feet of freeboard
- Sweep streets daily if visible soil material is carried out from the construction site

Similarly, ozone precursor emissions (ROG and NO<sub>x</sub>) are calculated to be below SCAQMD CEQA thresholds. However, because of the regional non-attainment for photochemical smog, the use of reasonably available control measures for diesel exhaust is recommended. Combustion emissions control options include:

### **Exhaust Emissions Control**

- Utilize well-tuned off-road construction equipment.
- Establish a preference for contractors using Tier 3 or better rated heavy equipment.
- Enforce 5-minute idling limits for both on-road trucks and off-road equipment.

## GREENHOUSE GAS EMISSIONS

“Greenhouse gases” (so called because of their role in trapping heat near the surface of the earth) emitted by human activity are implicated in global climate change, commonly referred to as “global warming.” These greenhouse gases contribute to an increase in the temperature of the earth’s atmosphere by transparency to short wavelength visible sunlight, but near opacity to outgoing terrestrial long wavelength heat radiation in some parts of the infrared spectrum. The principal greenhouse gases (GHGs) are carbon dioxide, methane, nitrous oxide, ozone, and water vapor. For purposes of planning and regulation, Section 15364.5 of the California Code of Regulations defines GHGs to include carbon dioxide, methane, nitrous oxide, hydrofluorocarbons, perfluorocarbons and sulfur hexafluoride. Fossil fuel consumption in the transportation sector (on-road motor vehicles, off-highway mobile sources, and aircraft) is the single largest source of GHG emissions, accounting for approximately half of GHG emissions globally. Industrial and commercial sources are the second largest contributors of GHG emissions with about one-fourth of total emissions.

California has passed several bills and the Governor has signed at least three executive orders regarding greenhouse gases. GHG statutes and executive orders (EO) include AB 32, SB 1368, EO S-03-05, EO S-20-06 and EO S-01-07.

AB 32 is one of the most significant pieces of environmental legislation that California has adopted. Among other things, it is designed to maintain California’s reputation as a “national and international leader on energy conservation and environmental stewardship.” It will have wide-ranging effects on California businesses and lifestyles as well as far reaching effects on other states and countries. A unique aspect of AB 32, beyond its broad and wide-ranging mandatory provisions and dramatic GHG reductions are the short time frames within which it must be implemented. Major components of the AB 32 include:

- Require the monitoring and reporting of GHG emissions beginning with sources or categories of sources that contribute the most to statewide emissions.
- Requires immediate “early action” control programs on the most readily controlled GHG sources.
- Mandates that by 2020, California’s GHG emissions be reduced to 1990 levels.
- Forces an overall reduction of GHG gases in California by 25-40%, from business as usual, to be achieved by 2020.
- Must complement efforts to achieve and maintain federal and state ambient air quality standards and to reduce toxic air contaminants.

Statewide, the framework for developing the implementing regulations for AB 32 is under way. Maximum GHG reductions are expected to derive from increased vehicle fuel efficiency, from greater use of renewable energy and from increased structural energy efficiency. Additionally, through the California Climate Action Registry (CCAR now called the Climate Action Reserve), general and industry-specific protocols for assessing and reporting GHG emissions have been

developed. GHG sources are categorized into direct sources (i.e. company owned) and indirect sources (i.e. not company owned). Direct sources include combustion emissions from on-and off-road mobile sources, and fugitive emissions. Indirect sources include off-site electricity generation and non-company owned mobile sources.

## **THRESHOLDS OF SIGNIFICANCE**

In response to the requirements of SB97, the State Resources Agency developed guidelines for the treatment of GHG emissions under CEQA. These new guidelines became state laws as part of Title 14 of the California Code of Regulations in March, 2010. The CEQA Appendix G guidelines were modified to include GHG as a required analysis element. A project would have a potentially significant impact if it:

- Generates GHG emissions, directly or indirectly, that may have a significant impact on the environment, or,
- Conflicts with an applicable plan, policy or regulation adopted to reduce GHG emissions.

Section 15064.4 of the Code specifies how significance of GHG emissions is to be evaluated. The process is broken down into quantification of project-related GHG emissions, making a determination of significance, and specification of any appropriate mitigation if impacts are found to be potentially significant. At each of these steps, the new GHG guidelines afford the lead agency with substantial flexibility.

Emissions identification may be quantitative, qualitative or based on performance standards. CEQA guidelines allow the lead agency to “select the model or methodology it considers most appropriate.” The most common practice for transportation/combustion GHG emissions quantification is to use a computer model such as CalEEMod, as was used in the ensuing analysis.

The significance of those emissions then must be evaluated; the selection of a threshold of significance must take into consideration what level of GHG emissions would be cumulatively considerable. The guidelines are clear that they do not support a zero net emissions threshold. If the lead agency does not have sufficient expertise in evaluating GHG impacts, it may rely on thresholds adopted by an agency with greater expertise.

On December 5, 2008 the SCAQMD Governing Board adopted an Interim quantitative GHG Significance Threshold for industrial projects where the SCAQMD is the lead agency (e.g., stationary source permit projects, rules, plans, etc.) of 10,000 Metric Tons (MT) CO<sub>2</sub> equivalent/year. In September 2010, the SCAQMD CEQA Significance Thresholds GHG Working Group released revisions which recommended a threshold of 3,000 MT CO<sub>2</sub>e for all land use projects. This 3,000 MT/year recommendation has been used as a guideline for this analysis. In the absence of an adopted numerical threshold of significance, project related GHG emissions in excess of the guideline level are presumed to trigger a requirement for enhanced GHG reduction at the project level.

## PROJECT RELATED GHG EMISSIONS GENERATION

### Construction Activity GHG Emissions

Project construction is assumed to occur over a single calendar year. During project construction, the computer model predicts that the construction activities will generate the CO<sub>2</sub>e emissions identified in Table 10.

**Table 10**  
**Construction Emissions (Metric Tons CO<sub>2</sub>e)**

	CO <sub>2</sub> e
Year 2024	72.2
<b>Amortized</b>	<b>2.4</b>

CalEEMod Output provided in appendix

SCAQMD GHG emissions policy from construction activities is to amortize emissions over a 30-year lifetime. The amortized level is also provided. GHG impacts from construction are considered individually less-than-significant.

### Project Operational GHG Emissions

The input assumptions for operational GHG emissions calculations, and the GHG conversion from consumption to annual regional CO<sub>2</sub>e emissions are summarized in the modeling output files found in the appendix of this report.

The total operational and annualized construction emissions for the proposed project are identified in Table 11. The project GHG emissions are considered less-than-significant.

**Table 11**  
**Operational Emissions**  
**(Metric Tons CO<sub>2</sub>e)**

Consumption Source	
Area Sources	6.8
Energy Utilization	41.1
Mobile Source	102.4
Solid Waste Generation	6.7
Water Consumption	9.3
Construction	2.4
<b>Total</b>	<b>168.7</b>
Guideline Threshold	3,000

## **CONSISTENCY WITH GHG PLANS, PROGRAMS AND POLICIES**

The City of Fountain Valley has not yet completed a finalized Greenhouse Gas Reduction Plan. The applicable GHG planning document is AB-32. As discussed above, the project is not expected to result in a significant increase in GHG emissions. As a result, the project results in GHG emissions below the recommended SCAQMD 3,000-ton ..threshold. Therefore, the project would not conflict with any applicable plan, policy, or regulation to reduce GHG emissions.

## **CALEEMOD2020.4.0 COMPUTER MODEL OUTPUT**

- **DAILY EMISIONS**
- **ANNUAL EMISSIONS**